



Material Safety Data Sheet

Product #'s: PPC-32(SKU No. 2207030)
PPC-1G (SKU No. 2207040)

MSDS #: RTT-PR-004 Rev. # 1

Rev. Date: 5/02/2008

1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Product Name: PREMA Pre-Buff Cleaner

Manufacturer: PREMA Products, Inc., 1500 Industrial Blvd., Madison, GA 30650

24-Hour Emergency Phone Number: North America: 800-424-9300 (CHEMTREC)
International: 703-527-3887 (CHEMTREC) Collect Calls Accepted

2. PRODUCT INGREDIENTS

<u>CHEMICAL NAME:</u>	<u>CAS NUMBER:</u>	<u>% RANGE:</u>	<u>OSHA PEL:</u>
Heptane (n-)	142-82-5	80-85	500 ppm TWA; 2000 mg/m ³ TWA
Acetone	67-64-1	15-20	1000 ppm TWA; 2400 mg/m ³ TWA

Component Related Regulatory Information

This product may be regulated, have exposure limits or other information identified as the following: Rubber solvent (Naphtha), Ketones, liquid, n.o.s.

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication). The balance of ingredients not rated as hazardous as defined in 29 CFR 1910.1200. This product is regulated under the Canadian Controlled Products Regulations.

Remainder of components are either non-hazardous or below regulatory requirements.

3. HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS:

The product is a milky, opaque liquid with a light hydrocarbon odor. **EXTREMELY FLAMMABLE** liquid. This product is harmful by inhalation, when in contact with the skin, eyes and if it is swallowed. Keep this product away from heat, sparks, or open flame.

EYE: This product may cause irritation to the eyes. Vapors may also produce eye irritation. Contact may cause stinging, watering, and redness.

SKIN: This product may cause irritation to the skin. Contact may cause redness, itching, burning, and skin damage. Prolonged or repeated contact with this product may dry and/or defat the skin. A single exposure is not likely to result in the product being absorbed through the skin in harmful amounts.

INGESTION: Ingestion can cause vomiting. If aspirated (liquid enters the lung), the product may be rapidly absorbed through the lungs and can result in chemical pneumonitis. (DO NOT INDUCE VOMITING.)

INHALATION: This product may be harmful by inhalation. Vapors of this product may cause irritation of the nose, throat, and respiratory tract. Inhalation of vapors can cause CNS depression including headache, nausea, dizziness and incoordination.



Material Safety Data Sheet

Product #'s: PPC-32(SKU No. 2207030)
PPC-1G (SKU No. 2207040)

MSDS #: RTT-PR-004 Rev. # 1

Rev. Date: 5/02/2008

4. FIRST AID

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. If irritation persists get medical attention.

SKIN: For skin contact, flush with large amounts of water while removing contaminated clothing. Wash affected area with mild soap and water. If irritation persists, get medical attention. Wash contaminated clothing before reuse.

INGESTION: Aspiration hazard: If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Do not induce vomiting. Call a physician immediately.

INHALATION: If inhaled, immediately remove the affected person to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Seek medical attention.

NOTE TO PHYSICIAN: Provide general supportive measures and treat symptomatically.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES:

Flash Point: -4 °F (-20.2 °C)

Upper Flammable Limit (UFL): 13.2 (% Volume in Air)

Auto Ignition: 399.0 °F (203.8 °C)

Method Used: TCC

Lower Flammable Limit (LFL): 1.1 (% Volume in Air)

Flammability Classification: Class 1B

HAZARDOUS COMBUSTION PRODUCTS: Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

EXTINGUISHING MEDIA: Dry chemical, foam, carbon dioxide.

FIRE FIGHTING INSTRUCTIONS: DANGER, EXTREMELY FLAMMABLE! Clear fire area of unprotected personnel and isolate. Vapors are heavier than air and may travel along the ground to some distant source of ignition and flash back. Avoid accumulation of water. Floating product may reignite on the surface of the water.

PROTECTIVE EQUIPMENT FOR FIRE FIGHTERS: Firefighters should wear full-face, self-contained breathing apparatus and impervious protective clothing.

6. ACCIDENTAL RELEASE MEASURES

CONTAINMENT PROCEDURES: Eliminate all sources of ignition or flammables that may come into contact with a spill of this material. Handling equipment must be grounded to prevent sparking. Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible.

CLEAN-UP PROCEDURES: Eliminate ignition sources including sources of electrical, static or frictional sparks. Ventilate the contaminated area. Absorb spill with inert material. Shovel material into properly labeled closed metal containers for disposal. Place in non-leaking containers for immediate disposal. Flush area with water to remove trace residue. Do not allow the spilled product to enter public drainage system or open watercourses.

EVACUATION PROCEDURES: Persons not wearing appropriate protective equipment should be excluded from area of spill until clean up has been completed.



Material Safety Data Sheet

**Product #'s: PPC-32(SKU No. 2207030)
PPC-1G (SKU No. 2207040)**

MSDS #: RTT-PR-004 Rev. # 1

Rev. Date: 5/02/2008

SPECIAL PROCEDURES: Follow all Local, State, Federal and Provincial regulations for disposal. Notify the proper authorities if entry to the environment occurs.

7. HANDLING & STORAGE

HANDLING: Keep liquid and vapor away from heat, sparks and flames. Surfaces that are sufficiently hot may ignite liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone. Vapors may accumulate and travel to ignition sources distant from the handling site; flash fire can result. Keep containers closed when not in use. Use with adequate ventilation.

Containers, even those that have been emptied, can contain explosive vapors. DO NOT cut, drill, grind, weld or perform similar operations on or near containers. DO NOT pressurize drum containers to empty them.

Static electricity may accumulate and create a fire hazard. Ground fixed equipment. Bond and ground transfer containers and equipment.

Wash with soap and water before eating, drinking, smoking, applying cosmetics, or using toilet facilities. Air-dry contaminated clothing in a well ventilated area before laundering.

STORAGE: Keep packaged in original, labeled containers until use. Store in a cool, dry, well-ventilated area. Store this product in airtight containers away from sources of heat and light. Ground all equipment to prevent accumulation of static charge. Store away from incompatible materials. Do not remove or deface label. Do not reuse container without recycling or reconditioning in accordance with any Federal, Provincial, State or local laws. Do not use cutting or welding torches, open flames, or electric arcs on empty or full containers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION: Wear safety glasses. Chemical goggles and/ or face shields should be worn, when splashing is a possibility. Contact lenses should not be exposed. If vapor exposure causes eye discomfort, use a full-face respirator.

SKIN PROTECTION: Use impervious gloves. Use of impervious apron and boots are recommended. Wash contaminated clothing before reuse.

RESPIRATORY PROTECTION: If recommended exposure limits are exceeded, a NIOSH-approved, continuous flow supplied air-respirator, hood or helmet is acceptable.

EXPOSURE GUIDELINE(s):



Material Safety Data Sheet

Product #'s: **PPC-32(SKU No. 2207030)**
PPC-1G (SKU No. 2207040)

MSDS #: RTT-PR-004 Rev. # 1

Rev. Date: 5/02/2008

Component Exposure Limits

PREMA Products Inc. recommends that its customers minimize employee exposure. REMA therefore suggests that its customers consider adopting the lower of the current OSHA PEL or the ACGIH TLV's for the purpose of evaluating employee exposures. The TLV's recommended by the ACGIH have been updated on a continuing basis.

Heptane (n-) (142-82-5)

ACGIH:	400 ppm TWA 500 ppm STEL
OSHA:	500 ppm TWA; 2000 mg/m ³ TWA
NIOSH:	85 ppm TWA; 350 mg/m ³ TWA 440 ppm Ceiling (15 min); 1800 mg/m ³ Ceiling (15 min)

Acetone (67-64-1)

ACGIH:	500 ppm TWA 750 ppm STEL
OSHA:	1000 ppm TWA; 2400 mg/m ³ TWA
NIOSH:	250 ppm TWA; 590 mg/m ³ TWA

Component Exposure Limits – Canada

The following Provincial Exposure Limits apply for this product's components.



Material Safety Data Sheet

Product #'s: **PPC-32(SKU No. 2207030)**
PPC-1G (SKU No. 2207040)

MSDS #: RTT-PR-004 Rev. # 1

Rev. Date: 5/02/2008

Heptane (n-) (142-82-5)

Alberta:	400 ppm TWA; 1640 mg/m ³ TWA 500 ppm STEL; 2050 mg/m ³ STEL
British Columbia:	400 ppm TWA 500 ppm STEL
Manitoba:	400 ppm TWA; 1600 mg/m ³ TWA 500 ppm STEL; 2000 mg/m ³ STEL
New Brunswick:	400 ppm TWA; 1640 mg/m ³ TWA 500 ppm STEL; 2050 mg/m ³ STEL
NW Territories:	400 ppm TWA; 1640 mg/m ³ TWA 500 ppm STEL; 2049 mg/m ³ STEL
Nova Scotia:	400 ppm TWA 500 ppm STEL
Nunavut:	400 ppm TWA; 1640 mg/m ³ TWA 500 ppm STEL; 2049 mg/m ³ STEL
Ontario:	400 ppm TWAEV; 1635 mg/m ³ TWAEV 500 ppm STEV; 2045 mg/m ³ STEV
Quebec:	400 ppm TWAEV; 1640 mg/m ³ TWAEV 500 ppm STEV; 2050 mg/m ³ STEV
Saskatchewan:	1640 mg/m ³ TWA; 400 ppm TWA 2050 mg/m ³ STEL; 500 ppm STEL
Yukon:	400 ppm TWA; 1600 mg/m ³ TWA 500 ppm STEL; 2000 mg/m ³ STEL

Acetone (67-64-1)

Alberta:	750 ppm TWA; 1800 mg/m ³ TWA 1000 ppm STEL; 2400 mg/m ³ STEL
British Columbia:	250 ppm TWA 500 ppm STEL
Manitoba:	750 ppm TWA; 1780 mg/m ³ TWA 1000 ppm STEL; 2375 mg/m ³ STEL
New Brunswick:	500 ppm TWA; 1188 mg/m ³ TWA 750 ppm STEL; 1782 mg/m ³ STEL
NW Territories:	1000 ppm TWA; 2370 mg/m ³ TWA 1250 ppm STEL; 2970 mg/m ³ STEL
Nova Scotia:	500 ppm TWA 750 ppm STEL
Nunavut:	1000 ppm TWA; 2370 mg/m ³ TWA 1250 ppm STEL; 2970 mg/m ³ STEL
Ontario:	500 ppm TWAEV 750 ppm STEV
Quebec:	750 ppm TWAEV; 1780 mg/m ³ TWAEV 1000 ppm STEV; 2380 mg/m ³ STEV
Saskatchewan:	1780 mg/m ³ TWA; 750 ppm TWA 2380 mg/m ³ STEL; 1000 ppm STEL
Yukon:	1000 ppm TWA; 2400 mg/m ³ TWA 1250 ppm STEL; 3000 mg/m ³ STEL



Material Safety Data Sheet

Product #'s: PPC-32(SKU No. 2207030)
PPC-1G (SKU No. 2207040)

MSDS #: RTT-PR-004 Rev. # 1

Rev. Date: 5/02/2008

9. PHYSICAL & CHEMICAL PROPERTIES

APPEARANCE: Clear

ODOR: Light Hydrocarbon **ODOR THRESHOLD:** Not Available

BOILING POINT: 133-200 °F (56.6-93.3 °C) @ 760 mmHg (Concentrate only)

SOLUBILITY IN WATER: <25%

SPECIFIC GRAVITY: 0.673 @ 77 °F (Concentrate only)

VAPOR PRESSURE: 186 mm Hg @ 68.00 °F (for product)

% VOLATILE: 676 g/l less 135 g/l (exempt VOC)

10. STABILITY & REACTIVITY

INCOMPATIBILITY WITH OTHER MATERIALS: This product may react with strong oxidizing agents.

HAZARDOUS POLYMERIZATION: Will not occur.

DECOMPOSITION PRODUCTS: Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Through inhalation, ingestion or passage of the material through the skin the following symptoms may occur: stomach or intestinal upset (nausea, vomiting, diarrhea); irritation (nose, throat, airway); central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness); temporary changes in mood and behavior; loss of appetite; loss of coordination; irregular heartbeat; narcosis (dazed or sluggish feeling).

CHRONIC TOXICITY

Prolonged or repeated liquid contact can result in defatting and drying of the skin, which may result in skin irritation and dermatitis.

CARCINOGENICITY

No carcinogenicity data available for this product.

Component Carcinogenicity

Acetone (67-64-1)

ACGIH:

A4 - Not Classifiable as a Human Carcinogen



Material Safety Data Sheet

Product #'s: PPC-32(SKU No. 2207030)
PPC-1G (SKU No. 2207040)

MSDS #: RTT-PR-004

Rev. # 1

Rev. Date: 5/02/2008

12. ECOLOGICAL INFORMATION

This product is toxic to aquatic organisms. This product may cause long-term adverse effects in the aquatic environment.

Component Analysis - Ecotoxicity - Aquatic Toxicity

Heptane (n-) (142-82-5)

Test & Species		Conditions
24 Hr LC50 goldfish	4.0 mg/L	
24 Hr LC50 mosquito fish	4900 mg/L	
96 Hr LC50 cichlid fish	375.0 mg/L	

Acetone (67-64-1)

Test & Species		Conditions
96 Hr LC50 rainbow trout	5540 mg/L	static
96 Hr LC50 fathead minnow	6210 mg/L	flow-through
96 Hr LC50 bluegill	8300 mg/L	static
48 Hr LC50 water flea	0.0039 mg/L	
48 Hr EC50 water flea	12700 mg/L	Static

13. DISPOSAL CONSIDERATIONS

DISPOSAL: Waste must be handled in accordance with all federal, state, provincial, and local regulations.

UNUSED & UNCONTAMINATED PRODUCT:

Component Waste Numbers

Acetone (67-64-1)

RCRA: waste number U002 (Ignitable waste)

D001 (ignitable)

This is a characteristic waste 1D.

14. TRANSPORT INFORMATION

US DOT Information

Shipping Name: Flammable liquids, n.o.s. (Contains: Heptane (n-))

UN/NA #: UN1993 **Hazard Class:** 3 **Packing Group:** II

Required Label(s): Flammable Liquid

Additional Info.: PLACARD (WHEN REQUIRED): FLAMMABLE LIQUID, 3

EXCEPTIONS: DOT Paragraphs 173.150, 173.202, & 173.242.

ALTERNATE SHIPPING ARRANGEMENTS: Based on package or shipping container size, this product may be shipped as a, "Limited Quantity", or, renamed, "Consumer Commodity" and reclassified as, "ORM-D" Material.

TDG Information

Shipping Name: Flammable liquid, n.o.s. (Contains: Heptane (n-))

UN/NA #: UN1993 **Hazard Class:** 3 **Packing Group:** II

Required Label(s): Flammable Liquid

IMDG Information

Additional Info.: EmS No = F-E, S-E

Exceptions: For package and container size when shipped as limited quantity under packaging instruction P001, revision PPI and Chapter 3.4 (Limited Quantity).



Material Safety Data Sheet

Product #'s: PPC-32(SKU No. 2207030)
PPC-1G (SKU No. 2207040)

MSDS #: RTT-PR-004 Rev. # 1

Rev. Date: 5/02/2008

IATA Information
Additional Info.: 3

15. REGULATORY INFORMATION

US FEDERAL REGULATIONS

SARA 313 INFORMATION:

Component Analysis

None of this products components are listed under SARA Section 313 (40 CFR 372.65).

SARA HAZARD CATEGORY:

Acute Health: Yes Chronic Health: Yes Fire: Yes Pressure: No Reactive: No

COMPREHENSIVE ENVIRONMENTAL RESPONSE COMPENSATION AND LIABILITY ACT (CERCLA):

Component Analysis

This material contains one or more of the following chemicals required to be identified under CERCLA (40 CFR 302.4).

Acetone (67-64-1)

CERCLA: 5000 lb final RQ; 2270 kg final RQ

TOXIC SUBSTANCES CONTROL ACT (TSCA): All components are on the U.S. EPA TSCA Inventory List.

Component Analysis - Inventory

Component	CAS #	TSCA	CAN	EEC
Heptane (n-)	142-82-5	Yes	DSL	EINECS
Acetone	67-64-1	Yes	DSL	EINECS

STATE RIGHT-TO-KNOW:

Component Analysis - State

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA	RI
Heptane (n-)	142-82-5	Yes	Yes	Yes	Yes	Yes	Yes
Acetone	67-64-1	Yes	Yes	Yes	Yes	Yes	Yes



Material Safety Data Sheet

Product #'s: PPC-32(SKU No. 2207030)
PPC-1G (SKU No. 2207040)

MSDS #: RTT-PR-004 Rev. # 1

Rev. Date: 5/02/2008

CANADIAN REGULATIONS

WHMIS INFORMATION:

WHMIS Classification: B2, D2B

Component Analysis - WHMIS IDL

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

Component	CAS #	Minimum Concentration
Heptane (n-)	142-82-5	1 %
Acetone	67-64-1	1 %

EUROPE:

Component Analysis

Component (CAS#)	EC #
Heptane (n-) (142-82-5)	205-563-8
Acetone (67-64-1)	200-662-2

16. OTHER INFORMATION

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) RATINGS:

NFPA Ratings: Health: 1 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

MEDICAL EMERGENCIES:

Call CHEMTREC 24 hours a
Day for emergency information
(800-424-9300)

FOR ANY OTHER INFORMATION:

PREMA Products Inc.
1500 Industrial Blvd.
Madison, GA 30650

NOTICE: PREMA Products Inc. believes that the information contained on this material safety data sheet is accurate. The suggested procedures are based on experience as of the date of publication. They are not necessarily all-inclusive nor fully adequate in every circumstance. Also, the suggestions should not be confused with nor followed in violation of applicable laws, regulations, rules or insurance requirements.

NO WARRANTY IS MADE, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE.