

Ken-Tool[®]

WHEREVER TIRES ARE CHANGED[™]

Catalog KT0413

Supersedes Catalog No. KT0411

TRUCK TIRE SERVICE





About Ken-Tool

Ken-Tool is the leading manufacturer of tire service tools in the world. Headquartered in Akron, Ohio, Ken-Tool has been providing the tire industry and automotive aftermarket with quality products for over 90 years.

A lot of change has occurred within Ken-Tool over the years. But its long-time tag-line, "Wherever Tires Are Changed", has held true. Ken-Tool's brand name and reputation remain the best in the tire-service industry, and it is the passion of the company's leaders to make sure that continues to be true in the years ahead.

Housed in a 70,000 square foot facility, Ken-Tool is a primary manufacturer of hand-tool products, with its manufacturing expertise centered on drop hammer, up-setter and press forgings. The company goes to market through the traditional aftermarket distribution network.



Throughout this catalog watch for YouTube symbols that indicate one or more videos are available for the product you are reviewing. Then go to www.youtube.com/kentoolvideomedia to find a selection of videos for our products. You can also scan the barcode with your Smartphone to get a link to our YouTube videos or details on how to Contact Us at Ken-Tool.



768 E. North St., Akron, Ohio 44305
Phone: 330-535-7177 • Fax: 330-535-1345
Visit our web site at: www.kentool.com

New Products

reCore™ TPMS Sensor Saver System	3
Blue Cobra® Truck Tire Service Set.....	4
Mega Airblast™ Bead Seater	5
EarthMover Tire Inflation Cage	6
Dual Wheel Separator	7
ValveCapper®	8
Strap Winder	9
Socket Sets.....	10
Extra Leverage Extension Handle	28
Bendix Air Disc Brake Tool Kits.....	44

Pro Super Hub-Shark® (7326)

Vises & C-Clamps

Pro Workshop Vises	34
Professional C-Clamps	34

Serpent™ Tire Changing Sets

Serpent™ Mount & Demount Tools	13, 14
Super Serpent™ Mount & Demount Tools	13, 14

Bendix Air Disc Brake Tools

Tappet & Boot Replacement Tool Kit	44
Guide Pin / Pin Boot Service Tool Kit	44

Ken-Tool®

Aligning Bars	43
Aluminum Wheel Protector.....	4, 11, 13, 14, 18
Ball Joint Separator	42
Bead Breakers	
ATV	22
Driving Iron	19
Floor Type.....	19
Impact	19
Portable.....	19
Truck/Farm/OTR	19
Wedges.....	20
Bead Expanders, Pneumatic	24
Bead Holders	
Aluminum Bead Holders	4, 11, 18
Bead Holder for 19.5" Aluminum Wheels	11, 18
Brass Bead Holding Device	11, 13, 14, 18
Bead Seaters.....	22, 24
C-Clamps	34
Center Cap Removers	
Wide Blade	25
Narrow Blade	25
Chrome Lug Nut Cover Remover	25
Dual Wheel Stud Remover	40
Easy-Lift™ Bead Seating Stand.....	32
Front End Tools	
Ball Joint Separator	42
Pitman Arm Wedge.....	42
Separator Tool	42
Shock Link/Tie Rod Separator	42
Hammers	
Cross-Pein/Blacksmith	43
Dead Blow	43
Epoxy Kits.....	21
General Purpose	21
Heavy-Duty	21
New England Hand Drilling.....	43
Replacement Rubber Heads	21
Rubber Mallet.....	43
Sledge	43
Handles	
Aluminum, Fiberglass, Wood	21
Heavy-Duty Double-End Spoons.....	15
Impact Separator Tool	42
Industrial Lock-Ring Tools	17
IronMan™ Ergonomic Wheel Lifting Bar.....	18
Leak Locator.....	23
Leverage Bar.....	28, 19
Lock Ring Tools	17
Tire & Bead Lubricant.....	23

Manual Tire Changers for Small Tires.....	22
Pitman Arm Wedge	42
Rim Guard	28
Separator Tool	42
Shock Link/Tie Rod Separator	42
Sockets	
Flip Sockets	38, 39, 40
Heavy-Duty Impact	40
Socket Sets.....	35, 36, 37, 38, 39
Twist Sockets	37, 38
Specialty Sockets, Torque Sticks & Extensions	35, 36, 37, 38, 39, 40
Spring Compressor, McPherson Strut	42
Swab, Bead Lubricant.....	23
Tire & Wheel Service Center	29, 30
Tire Tool & Lug Wrench Merchandisers	29, 30
Tire Changing Stand	32
Tire Inflation Cages	6, 32
Blue Cobra® Truck Tire Demount Tool	4, 11
Tire Irons (Mount/Demount)	
European Style	16
Heavy-Duty Truck (T45A®, T45AC™, T45AS, T45HD, T47A).....	12
Motorcycle/Small Wheel	16
Nineteen-Five™ Tire Mount/Demount Set.....	11
Tire Snakes®	22
Tubeless	12
Tire Knockers	43
Tire Mount/Demount Lubricant.....	23
Tire Spoons	
Curved	15, 16
Curved w/Flat Tip	15
Drop-Center	15, 16
Heavy-Duty Double-End Spoons.....	15
Straight	15, 16
Tire Spreaders	24
Torque Master Torque Sticks & Extensions	35, 36
TPMS Sensor Hardware Service Set.....	41
Truck Wrench Handle	
Leverage Bar	28
Valve Breaker™.....	20
Valve Repair Tools	24
Vises	
Pro Reversible Mechanic's Vises	34
Pro Workshop Vises	34
Wedges	
Bead Breaking.....	20
Wheel Balancer.....	24
Wheel Cover Puller/Replacer	25
Wheel Lock Remover	40
Wheel Lock Remover Kit	37
Wheel Weight Tools.....	24
Wire Brush	24
Wrenches	
4-Way Lug Wrenches	
Folding.....	27
Heavy-Duty Truck	26
Light Truck/SUV.....	26, 27
OTR	26
Passenger Car	26, 27
Telescoping.....	27
Cap Nut	
Combination	25
Heavy-Duty	25
Ken-Tool Porkchop™	25
Double-End Truck	28
Power Wrench	27
Wrench Support Stand	28

NEW Look for this symbol beside individual product listings for exciting new tools from Ken Tool. All weights and measures are nominal. Variations in manufacture may occur.

Introducing the


reCore™

TPMS Sensor Saver System



Galvanic corrosion causes TPMS failures.

NOW YOU CAN REPAIR TPMS SENSORS WITHOUT EVEN TAKING THE TIRES OFF THE VEHICLE.



PATENT PENDING

Most TPMS sensor failures are caused by galvanic corrosion of the valve core and stem. This sounds like an easy fix — but until now, service techs could not, in most cases, replace the valve stem without replacing the entire sensor module, rebalancing the wheel, and resetting the TPMS sensor. Proven reliable in thousands of miles of real-world, all-season testing, the Ken-Tool reCore Sensor Saver System changes all that.

SIMPLE. The Ken-Tool reCore kit provides everything you need to drill out the corroded valve core, tap new threads, and install a new, corrosion-proof valve core and stem. No need to have the TPMS computer re-learn the module. No need to even remove the tire or wheel from the vehicle!

FAST. With a little skill, a tech can install a new valve stem in 10-15 minutes. Compare this to the time it takes to order a replacement TPMS module, install it, and reset the vehicle's TPMS system. And that's not to mention the cost savings you can pass on to the customer!

PROFITABLE. The Ken-Tool reCore TPMS Sensor Saver Kit will not only pay for itself after a few uses — it will provide you with great profit margins. And, since there are more than 200 million TPMS sensors on the road today, it opens the door to a high-potential market. The initial investment: just \$199 (suggested price)!

Introducing the

reCore™

TPMS Sensor Saver System

12-Piece Starter Kit #29980	If Your Per-Sensor Repair Fee Is:		
	\$39	\$49	\$59
Kit Cost	\$199	\$199	\$199
Revenue	\$468	\$588	\$708
Per kit Profit	\$269	\$389	\$509
Profit per Sensor	\$22.42	\$32.42	\$42.42
Your Profit % Is	57%	66%	72%

Ken-Tool's Patent Pending reCore Starter Kit (#29980) includes everything you need to service your TPMS Sensor replacement customers: 12 TPMS Sensor Savers, TPMS Valve Core Torque Tool (preset at 4-in-lbs), High Speed Dual Cutter Countersink Drill Bit, Tap, Tap Holder with T-handle, Bottle Ken-Lok™ Thread Sealant, Easy to follow instructions, Blow-molded plastic storage case.



29980

Introducing the

reCore™

TPMS Sensor Saver Refill Kit

25-Piece Refill Kit #29981	If Your Per-Sensor Repair Fee Is:		
	\$39	\$49	\$59
Refill Set Cost	\$199	\$199	\$199
Revenue	\$975	\$1225	\$1475
Per Set Profit	\$776	\$1026	\$1276
Profit per Sensor	\$31.04	\$41.04	\$51.04
Your Profit % Is	80%	64%	87%

Ken-Tool's Patent Pending reCore Refill Kit (#29981) includes 25 TPMS Sensor Savers plus a fresh Tap.

PATENT PENDING



29981



For product demo visit kentool.com/recore or scan the QR code with your mobile device.

NEW

Ken-Tool®

WHEREVER TIRES ARE CHANGED™

BLUE COBRA® TRUCK TIRE SERVICE SET

All the tools you need for changing 22.5" & 24.5"
truck tires in one convenient set!



The 35442 Blue Cobra® Truck Tire Service Set contains all the tools you need to change most 22.5" and 24.5" tubeless truck tires quickly and easily.

Set No. 35442 Weight: 40 Lbs (18.2 kg).

8 Pc. Set Includes:

Model	Description	Length	Weight	Quantity
35440	Blue Cobra® Truck Tire Demount Tool	54"	22 lbs	1
34645C	T45AC Classic™ Tubeless Tire Iron	37"	4.6 lbs	1
33050	Double-End Tire Spoon	30"	1lb	1
35848	8 lb. Bucket Euro Paste Lube		8 lbs	1
30512	Euro-Style Lube applicator Brush	12"	.2 lbs	1
31713	Aluminum C-Lok™ Bead Holder	5.5"	.5 lbs each	2
31810	Leather Rim Protector	6"	.35 lbs	1

35442 Set ships in 1 box, UPS shippable.

**WATCH OUR VIDEOS ON
www.kentool.com
TO SEE 4 TRUCK TIRES
DEMOUNTED IN ABOUT A MINUTE!**



NEW

Ken-Tool®
WHEREVER TIRES ARE CHANGED™

BEAD SEATER



Bead Seating Tool

- **Used on Auto, ATV, and Truck Tires**
- **Designed for use on tires up to 24-1/2 diameter**
- **ASME-UM certified 5-gallon tank**
- **Heavy-duty bar valve quickly releases air between bead and rim**
- **Air pressure gauge and safety release valve included for operator convenience and safety**
- **Plastic nose clip protects chrome and alloy wheels; replacements available**

Model	Description	Weight
31444	Bead Seating Tool with 5 Gallon Tank	33.1 lbs (15 kg)

Outil de portée de talon

- **Utilisé sur les pneus d'automobiles, de véhicules tout-terrain et de camions**
- **Conçu pour utilisation sur des pneus jusqu'à 24,5 pouces de diamètre**
- **Réservoir 5 gallons (19 litres) certifié ASME-UM**
- **Une robuste valve à tige libère rapidement l'air entre le talon et la jante**
- **Manomètre et soupape de sécurité inclus pour plus de commodité et de sécurité pour l'opérateur**
- **Un pince-nez en plastique protège les jantes alliage et chromées ; remplacements disponibles**

Herramienta para calzado de talone

- **Se utiliza en neumáticos de automóviles, vehículos todo terreno (ATV) y camiones**
- **Diseñada para utilizarse en neumáticos de hasta 24-1/2 de diámetro**
- **Tanque de 5 galones con certificación ASME-UM**
- **La válvula de barra de alta resistencia libera aire rápidamente entre el talón del neumático y la llanta**
- **Se incluye un manómetro de presión de aire y una válvula de descarga para comodidad y seguridad al operador**
- **La abrazadera plástica protege las ruedas de cromo y aleación. Hay repuestos disponibles**

WATCH OUR VIDEOS ON
www.kentool.com



KEN-TOOL • 768 E. North Street, Akron, OH 44305

Toll Free: 888-536-8665 • Fax: 800-872-4929 • Phone: 330-535-7177 • Fax: 330-535-1345

E-mail: sales@kentool.com • www.kentool.com

KT081010

NEW

Ken-Tool®

WHEREVER TIRES ARE CHANGED™

EARTHMOVER TIRE INFLATION CAGE

Ken-Tool introduces the



“World’s Largest Single-Piece Inflation Cage”

Mandatory for any shop working with tubeless and multi-piece rims.

Guards against blown lock rings and rims.

Designed to meet OSHA reg. 29-CFR Part 1910.177 for restraining devices.

- **HD all steel cage protects workers, equipment and facilities**
- **For large Earthmover & Agricultural tires**
- **New patent pending design; with 10-bar construction**
- **Fits up to 29.5R25 L-3 Earthmover**
- **For maximum tire inflation pressure up to 100-psi**
- **Cage dimensions: 48" x 72" x 89"; ships on skid**
- **Proudly Made in USA**



Model	Item No.	Description	Weight
T111	36011	Earthmover Tire Inflation Cage	820 lbs (372 kg)



Watch our **EXPLOSION TESTING VIDEO** at 150-psi on www.kentool.com

Ken-Tool offers a complete line of tire cages — See page 31

KEN-TOOL • 768 E. North Street, Akron, OH 44305

Toll Free: 888-536-8665 • Fax: 800-872-4929 • Phone: 330-535-7177 • Fax: 330-535-1345

E-mail: sales@kentool.com • www.kentool.com

KT092812-EB

Ken-Tool® 6
WHEREVER TIRES ARE CHANGED™

NEW

Ken-Tool®

WHEREVER TIRES ARE CHANGED™

DUAL WHEEL SEPARATOR

Quickly & easily remove stuck or frozen dual steel wheels!!



Makes removing stuck or frozen dual steel wheels quick and easy. Ideal for use on nearly any truck, bus, van or trailer that has dual steel wheels.

- Innovative "One-piece" Pusher won't fall apart during use
- Pusher is ball bearing-driven for near-zero turning resistance
- Pusher is heat treated for long-lasting strength and durability
- Forcing Screw and Pullers have powerful 1-1/8" diameter x 11 threads for years of reliable service
- Includes two pullers to cover large truck, trailer and smaller light truck dual wheel applications
- Components have black oxide or bright nickel plating finish for rust and corrosion resistance
- Use with air or electric impact wrench
- Components are laser-etched for easy identification
- Comes in a sturdy, compact, easy to store case; 6.5" x 9.5" x 2.5", 5.3 lbs
- Proudly Made in USA
- Limited Lifetime Warranty



Dual Wheel Separator Demo Video #34549

Model	Description	Weight
34549	4 Pc. Dual Wheel Separator kit	5.3 lbs (2.4 kg)

KEN-TOOL • 768 E. North Street, Akron, OH 44305

Toll Free: 888-536-8665 • Fax: 800-872-4929 • Phone: 330-535-7177 • Fax: 330-535-1345

E-mail: sales@kentool.com • www.kentool.com

KT100212EB

7 Ken-Tool®
WHEREVER TIRES ARE CHANGED™

NEW

Ken-Tool®

WHEREVER TIRES ARE CHANGED™

VALVECAPPER®

2 TOOLS IN 1 – Cap and Core Remover



Ken-Tool® 29995
WHEREVER TIRES ARE CHANGED®

VALVECAPPER™

2 TOOLS IN 1
Cap and Core Remover

Makes it easier to check the inside dual tire

- Designed by a trucker to make a difficult job easier
- No more moving your rig to position valve stems just to get to the caps
- No more dropped caps — holds onto caps for removing and replacing
- At 11-1/2 inches it has enough reach to get the job done
- Unbreakable under normal use
- Designed for use on metal valve caps

For best results:
To remove: push tool onto cap while turning counter clock-wise.
To replace: turn cap clock-wise onto valve stem until cap is snug then pull tool off cap while turning clock-wise.
Do not store in direct sunlight as on dash.

YouTube 

© 2012 KEN-TOOL • AKRON, OH 44305 KT022212 FLT
TOLL FREE: 888-536-8665 • WWW.KENTOOL.COM



Makes it easier to check the inside dual tire

- Designed by a trucker to make a difficult job easier
- No more moving your rig to position valve stems just to get to the caps
- No more dropped caps - holds onto caps for removing and replacing
- At 11-1/2 inches it has enough reach to get the job done
- Unbreakable under normal use
- Designed for use on metal valve caps
- Shipped in convenient 25-piece counter display



WATCH OUR VIDEOS ON
www.kentool.com



29995 25 Pc. ValveCapper® Counter Display contains:

- Quantity: 25 Model No. 29995 ValveCappers
- Counter Display Unit
- Ship weight: 3 lbs (1.4 kg)

NEW


Ken-Tool®

WHEREVER TIRES ARE CHANGED™

STRAP WINDER

Patented design makes strap winding quick and easy!

Quick Wind



Quick Cheater Bar



Quick Tire Check



Three Tools In One!

- Patented design allows fast and easy strap winding with one hand
- Use to quickly tighten ratchet straps
- The perfect tire knocker
- Makes it easier to check the inside dual tire
- Steel construction is durable and provides long lasting service
- Foam rubber grip is comfortable even after repeated use
- Made in USA!



Part No.
39760

PATENTED



Strap Winder for
Trailers #39760

Model	Description	Length	Weight
39760	Strap Winder	19"	2.7 lbs (1.2 kg)

KEN-TOOL • 768 E. North Street, Akron, OH 44305

Toll Free: 888-536-8665 • Fax: 800-872-4929 • Phone: 330-535-7177 • Fax: 330-535-1345

E-mail: sales@kentool.com • www.kentool.com

KT041812EB

NEW

Ken-Tool®

WHEREVER TIRES ARE CHANGED™

SOCKET SETS

Made from Chrome-Moly Steel



30254 - 4 Pc. Lug Nut Remover Socket Set

Use for removing wheel locks or damaged lug nuts

Socket Sizes - 1/2" Drive:

- 30245-06 - 3/4" Socket
- 30245-07 - 13/16" Socket
- 30245-08 - 1" Socket
- 30245-09 - 1-1/8" Socket

Made in Taiwan

Model	Description	Weight
30245	4 Pc. Lug Nut Remover Socket Set	1.4 lbs (.6 kg)



30649 - 4 Pc. Heavy-Duty Wheel Stud Remover Set Inner Budd Nut & Wheel Stud Removal Set

Impact Socket Sizes:

- 30649-06 - 5/8" Socket
- 30649-07 - 3/4" Socket
- 30649-08 - Budd Wheel Inner Nut LH
- 30649-09 - Budd Wheel Inner Nut RH

- Removes damaged wheel studs and inner Budd nuts
- Internal tapered reverse threads lock onto damaged stud or nut and easily pulls off using impact wrench
- Wheel Stud Removers are 3/4" hex drive
- Budd Nut Removers are 1-1/8" hex drive

Made in Taiwan

Model	Description	Weight
30649	4 Pc. H.D. Wheel Stud Remover Set	3.5 lbs (1.6 kg)



30259 - 7 Pc. Thin-Wall Impact Socket Set

Non-Marring sockets for delicate wheels with minimal clearance for Car / Light Truck

Socket Sizes - 1/2" Drive:

- 30259-03 - 13/16" Socket
- 30259-04 - 7/8" Socket
- 30259-05 - 1" Socket
- 30259-06 - 1-1/16" Socket
- 30259-07 - 17 mm Socket
- 30259-08 - 19 mm Socket
- 30259-09 - 21 mm Socket

Made in Taiwan

Model	Description	Weight
30259	7 Pc. Thin-Wall Impact Socket Set	5 lbs (2.3 kg)



BLUE COBRA®

Truck Tire Demount Tool

Herramienta de desmontaje de neumáticos de camiones BLUE COBRA®


Outil de démontage de pneus de camion BLUE COBRA®

Quickly demount nearly any 22.5" and 24.5" tubeless truck tire, up to a 13" wide wheel. Ergonomic shaped steel handle with no-slip grip for optimum leverage while reducing back injuries. Solid steel Cobra head is press-fit into the steel handle — no fasteners to loosen or fall out. Allows demounting of the tire without lifting the entire wheel and tire off the ground — reduces back injuries. Aluminum bead support to grab the top bead of Super Single and Super Wide tires. 2 heavy-duty nylon rollers are easily replaced when worn, kit No. 35441 includes two rollers and two roll pins.

Model	Item No.	Length	Weight
35440	35440	54" (137 cm)	22 lbs (10 kg)

WATCH OUR VIDEO ON
www.kentool.com
TO SEE 4 TRUCK TIRES
DEMOUNTED IN ABOUT
A MINUTE!*

Special Bonus! Ken-Tool's patented leather wheel protector No. 31810 included to help protect expensive alloy wheels!



BLUE COBRA® Truck Tire Service Set

Juego de servicio de neumáticos de camiones BLUE COBRA®

Ensemble d'entretien de pneus de camion BLUE COBRA®



The 35442 Blue Cobra® Truck Tire Service Set contains all the tools you need to change most 22.5" & 24.5" tubeless truck tires quickly and easily.

Set No. 35442 Weight: 40 Lbs (18.2 kg).

8 Pc. Set Includes:

Model	Description	Quantity
35440	Blue Cobra® Truck Tire Demount Tool	1
34645C	T45AC Classic Tubeless Tire Iron	1
33050	Double-End Tire Spoon	1
35848	8 lb. Bucket Euro Paste Lube	1
30512	Euro-Style Lube Applicator Brush	1
31713	Aluminum C-Lok™ Bead Holder	2
31810	Leather Rim Protector	1



Blue Cobra®
Truck Tire
Demount Tool



* Blue Cobra®
Demounts 4
Truck Tires In
About A Minute



Blue Cobra®
Demounting A
385/ 65R22.5
Super Single




Blue Cobra®
Is So Easy To
Use Even a Girl
Can Do It

Nineteen-Five™ Tire Mounting & Demount Tool Set for 19.5" Tires

Juego de herramientas de montaje y desmontaje de neumáticos de 19.5" Nineteen-Five™

Jeu d'outils de montage - démontage de pneus de 19,5 po Nineteen-Five™

Part No. 33199 Mounting/Demounting Tool



Part No. 33196
Bead Holder for
19.5" Aluminum
Wheels



Tire Bars For
19.5 Tires & Wheels



Nineteen-Five™ Set:
How To Use It On A
19.5 Wheel

Part No. 31710 Bead Holder for Steel Wheels Part No. 31810 Aluminum Wheel Protector

19.5" tires must be mounted and demounted with the wheel's Hub Side Up because the Drop Center of the wheel is closer to the hub! This makes changing the 19.5" tires notoriously difficult because the hub gets in the way of conventional bars and spoons. 19.5" tires are also stiffer with high ply ratings and thick beads. Nineteen-Five™ bars are specially designed to work on the hub side to make your job easier, faster and safer! New tire bar uniquely designed to work on hubside of wheel — where hub protrudes above rim. Specially designed ends manipulate tire with less effort. Tools are powder coated to protect from rust and corrosion. Forged from high-grade carbon steel and heat-treated for long-lasting strength and durability. Specially designed Bead Holder to hold bead on 19.5" aluminum wheels.

Set No. 33195 Weight: 9.35 Lbs (4.25 kg).

5 Pc. Set Includes:

Model	Description	Length	Weight	Quantity
33199	Tire Mounting/Demounting Tool	38" (97 cm)	7 lbs (3.2 kg)	2
33196	Bead Holder for 19.5" Aluminum Wheels	7-1/2" (19 cm)	1 lb (.5 kg)	1
31710	Bead Holder for Steel Wheels - Solid Brass	4-1/2" (11.5 cm)	1 lb (.5 kg)	1
31810	Aluminum Wheel Protector - Leather	6" (15 cm)	.35 lbs (.15 kg)	1



Bent end
For mounting
and demounting
bottom bead



Curved end
For mounting
and demounting
top bead

Tubeless Truck Tire Mount / Demount Irons

Barras para montaje/desmontaje de llantas de camiones sin cámara

Démonte-pneu de montage/démontage pour pneus de camion sans chambre à air



Ken-Tool manufactures the largest and most diverse selection of tire mount/demount irons in the world. From the T45A® and T45AC Classic for standard truck tires, to the Serpent™ and Super Serpent™ Tire Changing Systems for wide-base Super Singles, Ken-Tool makes a tire iron for all your tire changing needs. Use on truck, agricultural, and industrial tires. One-piece manufacturing process and design assures long life and superior performance. Heat-treated for strength. Use in pairs. T45A® is a registered trademark of Ken-Tool.

Ken-Tool® brings back an old favorite – T45AC Classic™



Ken-Tool's patented designs offer one-piece construction, and assure long life for many tire-changing applications. Tip ends insert easily and will not cut or rip bead or sidewall. These designs make it easier to mount and demount tires without changing the way the tool is used.



T45AC Classic™ T45A



Mount end: Precision forged knob grips rim. New design won't slip during tire mounting. Special curve design always grabs the bead edge.



Demount end: Precision-forged angled tip slides between bead and rim easily. Forged design won't slip when demounting the second bead.

Model	Item No.	Length	Stock	Weight
T45A®	34645	37" (94 cm)	3/4" (19 mm)	4.6 lbs (2.1 kg)
T45AC™	34645C	37" (94 cm)	3/4" (19 mm)	4.6 lbs (2.1 kg)
NEW T45AS	34649	52" (132 cm)	7/8" (22mm)	9 lbs (4.1 kg)
T45HD	34647	41" (104 cm)	7/8" (22 mm)	7 lbs (3.2 kg)
T47A	34847	52" (132 cm)	1" (25 mm)	11 lbs (5 kg)

T45A-2000K™ Style Tubeless Tire Iron

Barra de hierro para montaje/desmontaje de neumáticos sin cámara estilo T45A-2000K™

Démonte-pneu pour pneus sans chambre à air T45A-2000K™



Design allows for less effort, provides excellent wheel/rim surface contact area for less side to side movement. Improved blade and knob design. Tip on one end for 'grabbing' the rim.

Model	Item No.	Length	Stock	Weight
T45A-2000K™	34644	37" (94 cm)	3/4" (19 mm)	5 lbs (2.2 kg)

Mount




Demount



Tubeless Tire Irons & Sets

Juegos y barras para llantas sin cámara

Démonte-pneus individuels & en ensemble pour pneus sans chambre à air



Sets provide all irons necessary for a variety of tire changing applications. Use "C" bar with the "B" extension bar for easier use on large, wide-base truck tires. Use on standard and large truck tires, including industrial, farm, buses, and tractors.

Standard • Estándar • Standard

Model	Item No.	Description	Length	Stock	Weight
T46	34746	Tire Iron Set includes: T46A,T46B,T46C		3/4" 19 mm	12 lbs 5.4 kg
T46A	34747	Straight Mount/Demount Tool	36" 91 cm	3/4" 19 mm	4.5 lbs 2 kg
T46B	34748	Straight Mount/Demount Tool "B" Extension for T46C	36" 91 cm	3/4" 19 mm	4.5 lbs 2 kg
T46C	34749	Offset Mount "C" Bar	22" 56 cm	3/4" 19 mm	3 lbs 1.4 kg

Heavy-Duty • De alta resistencia • Robuste

Model	Item No.	Description	Length	Stock	Weight
T47	34846	Tire Iron Set includes: T47A,T47B,T47C		1" 25 mm	29 lbs 13.1 kg
T47A	34847	Straight Mount/Demount Tool	52" 132 cm	1" 25 mm	11 lbs 5 kg
T47B	34848	Straight Mount/Demount Tool "B" Extension for T47C	49-1/2" 126 cm	1" 25 mm	11 lbs 5 kg
T47C	34849	Offset Mount "C" Bar	27" 69 cm	1" 25 mm	6.6 lbs 3 kg

Mounting



Demounting



Serpent™ Mount & Demount Tire Irons

Take the struggle out of mounting and demounting truck tires...
Everything you need to change tires easily and effortlessly.



Serpent™
Tubeless Tire Mount/
Demount Tire Irons



Serpent™
Bar To Demount An
11R22.5 Truck Tire
At MATS 2010

Serpent™ Demount Tool Herramienta de desmontaje Outil de démontage

"Makes demounting easier than ever."

Demounts **both** beads on most truck tires without the need for lifting the tire/wheel assembly off the ground, and then dropping it. Made of heat-treated alloy steel for maximum durability and strength. Patented.



Model	Item No.	Length	Stock	Weight
T2001	35449	39" (99 cm)	3/4" (19 mm)	6.5 lbs (3 kg)




Serpent™ Mount Tool Herramienta para montar Outil d'assemblage

"Makes mounting easier than ever."

Designed to stop against the rim, and then remove itself effortlessly from between the rim and bead. The small end of the tool easily gets under the stretched bead for that last pull. Patented.



Model	Item No.	Length	Stock	Weight
T2002	35450	38" (96 cm)	11/16" (17.5 mm)	4 lbs (1.8 kg)



Serpent™ 4 Pc. Tire Changing Set Juego de 4 piezas para cambiar llantas Ensemble 4 pièces de changement de pneu

Set No. 35453

Weight: 12 Lbs (5.4 kg). Patented.

4 Pc. Set Includes:

Model	Item No.	Qty.	Description
T2001	35449	1	Serpent Demount Tool
T2002	35450	1	Serpent Mount Tool
31710	31710	1	Brass Bead Holding device
31810	31810	1	Aluminum Wheel Protector

WATCH OUR VIDEOS ON
www.kentool.com



SUPER SERPENT™ Mount & Demount Tire Irons

Finally! Tools specially designed to handle big, big tires that actually work!
Now, mounting and demounting the biggest, heaviest truck tire is made easy.



Super Single Truck
Tire Mount/Dismount
Using Super Serpent™
Tire Tools



SuperSerpent™
Tbls Tire Mount/
Demount Tire
Irons

Super Serpent™ Mount Tool Herramienta para montar Outil d'assemblage

This mount tool for super singles only weighs about 6-1/2 pounds. It may seem "funny-looking", but every inch of this innovative design is purely serious. It makes interference of the second bead, while mounting the first, a thing of the past, and delivers **twice** the leverage of **any** "straight-type" tire mounting tool. It even has the small end that easily gets under the bead for that "last pull". Patented.



Super Serpent™
Mounting Tool Used To
Mount 21L-24 Backhoe

Model	Item No.	Length	Stock	Weight
T2005	35447	37" (94 cm)	3/4" (19 mm)	6.6 lbs (3 kg)





Super Serpent™ Demount Tool Herramienta de desmontaje Outil de démontage

Weighing in at only 5-1/2 pounds, this unique, lightweight demount tool for super singles can be lugged around on a fingertip, yet delivers the incredible leverage, right where it's needed, to easily pop those heavyweights right off their wheels. Patented.



Super Serpent™
Demounting Tool
Used To Demount
21L-24 Backhoe

Model	Item No.	Length	Stock	Weight
T2006	35448	37" (94 cm)	3/4" (19 mm)	5.5 lbs (2.5 kg)



Super Serpent™ 5 Pc. Tire Changing Set Juego de 5 piezas para cambiar llantas Ensemble 5 pièces de changement de pneu

Set No. 35446


Weight: 19 Lbs (8.6 kg). Patented.

5 Pc. Set Includes:

Model	Item No.	Qty.	Description
T2005	35447	1	Super Serpent Mount Tool
T2006	35448	1	Super Serpent Demount Tool
31710	31710	2	Brass Bead Holding device
31810	31810	1	Leather Wheel Protector

Mount Tool
T2005 (35447)

WATCH OUR VIDEOS ON www.kentool.com



Wheel Protector
31810
(see page 36)



Bead Holding Device
31710 Imported.
(see page 36)

Demount Tool
T2006 (35448)

Heavy-Duty Double-End Spoon Combinations


Combinaciones de cuchara de dos extremos de alta resistencia

Combinaisons robustes de cuillères à double extrémité



Use the 18" and 24" spoons to mount or demount passenger car, motorcycle, ATV, and light truck tires. The 30" spoons provide enough strength and leverage to work on large truck, bus, off-road vehicle, tractor, and aircraft tires. Constructed of premium-quality carbon steel, and heat-treated for long-lasting performance. Designed for fast and efficient tire changing. The highly versatile spoon often doubles as a mechanics helper wherever leverage is needed.

Many size and shape combinations available to meet your specific needs.




Straight / Curved Combination

Combinación recta/curva

Combinaison droite / courbe

Model	Item No.	Length	Stock	Weight
T1920Z18	31830	18" (46 cm)	9/16" (14 mm)	1.3 lbs (.6 kg)
T1920Y18	31840	18" (46 cm)	5/8" (16 mm)	1.6 lbs (.7 kg)
T1920X18	31850	18" (46 cm)	11/16" (17.5 mm)	1.8 lbs (.8 kg)
T1920Z24	32430	24" (61 cm)	9/16" (14 mm)	1.7 lbs (.8 kg)
T1920Y24	32440	24" (61 cm)	5/8" (16 mm)	2.1 lbs (1 kg)
T1920F24	32450	24" (61 cm)	11/16" (17.5 mm)	2.5 lbs (1.1 kg)
T1920A30	33050	30" (76 cm)	11/16" (17.5 mm)	3.1 lbs. (1.4 kg)
T1920M30	33060	30" (76 cm)	3/4" (19 mm)	3.4 lbs (1.5 kg)




Straight / Curved with Flat Tip Combination

Combinación recta/curva con punta plana

Combinaison droite / courbe avec embout plat

Model	Item No.	Length	Stock	Weight
T1922Z18	31831	18" (46 cm)	9/16" (14 mm)	1.3 lbs (.6 kg)
T1922Y18	31841	18" (46 cm)	5/8" (16 mm)	1.6 lbs (.7 kg)
T1922X18	31851	18" (46 cm)	11/16" (17.5 mm)	1.8 lbs (.8 kg)
T1922Z24	32431	24" (61 cm)	9/16" (14 mm)	1.7 lbs (.8 kg)
T1922Y24	32441	24" (61 cm)	5/8" (16 mm)	2.1 lbs (1 kg)
T1922F24	32451	24" (61 cm)	11/16" (17.5 mm)	2.5 lbs (1.1 kg)
T1922A30	33051	30"	11/16" (17.5 mm)	3.1 lbs. (1.4 kg)
T1922M30	33061	30"	3/4" (19 mm)	3.4 lbs (1.5 kg)




Curved / Curved with Flat Tip Combination

Combinación curva/curva con punta plana

Combinaison courbe / courbe avec embout plat

Model	Item No.	Length	Stock	Weight
T2022Z18	31832	18" (46 cm)	9/16" (14 mm)	1.3 lbs (.6 kg)
T2022Y18	31842	18" (46 cm)	5/8" (16 mm)	1.6 lbs (.7 kg)
T2022X18	31852	18" (46 cm)	11/16" (17.5 mm)	1.8 lbs (.8 kg)
T2022Z24	32432	24" (61 cm)	9/16" (14 mm)	1.7 lbs (.8 kg)
T2022Y24	32442	24" (61 cm)	5/8" (16 mm)	2.1 lbs (1 kg)
T2022F24	32452	24" (61 cm)	11/16" (17.5 mm)	2.5 lbs (1.1 kg)
T2022A30	33052	30" (76 cm)	11/16" (17.5 mm)	3.1 lbs. (1.4 kg)
T2022M30	33062	30" (76 cm)	3/4" (19 mm)	3.4 lbs (1.5 kg)




Straight / Drop-Center Combination

Combinación recta/centro rebajado

Combinaison droite / base creuse

Model	Item No.	Length	Stock	Weight
T1921Z18	31833	18" (46 cm)	9/16" (14 mm)	1.3 lbs (.6 kg)
T1921Y18	31843	18" (46 cm)	5/8" (16 mm)	1.6 lbs (.7 kg)
T1921X18	31853	18" (46 cm)	11/16" (17.5 mm)	1.8 lbs (.8 kg)
T1921Z24	32433	24" (61 cm)	9/16" (14 mm)	1.7 lbs (.8 kg)
T1921Y24	32443	24" (61 cm)	5/8" (16 mm)	2.1 lbs (1 kg)
T1921F24	32453	24" (61 cm)	11/16" (17.5 mm)	2.5 lbs (1.1 kg)
T1921A30	33053	30" (76 cm)	11/16" (17.5 mm)	3.1 lbs. (1.4 kg)
T1921M30	33063	30" (76 cm)	3/4" (19 mm)	3.4 lbs (1.5 kg)




Curved / Drop-Center Combination

Combinación curva/centro rebajado

Combinaison courbe / base creuse

Model	Item No.	Length	Stock	Weight
T2021Z18	31834	18" (46 cm)	9/16" (14 mm)	1.3 lbs (.6 kg)
T2021Y18	31844	18" (46 cm)	5/8" (16 mm)	1.6 lbs (.7 kg)
T2021X18	31854	18" (46 cm)	11/16" (17.5 mm)	1.8 lbs (.8 kg)
T2021Z24	32434	24" (61 cm)	9/16" (14 mm)	1.7 lbs (.8 kg)
T2021Y24	32444	24" (61 cm)	5/8" (16 mm)	2.1 lbs (1 kg)
T2021F24	32454	24" (61 cm)	11/16" (17.5 mm)	2.5 lbs (1.1 kg)
T2021A30	33054	30" (76 cm)	11/16" (17.5 mm)	3.1 lbs. (1.4 kg)
T2021M30	33064	30" (76 cm)	3/4" (19 mm)	3.4 lbs (1.5 kg)



Drop-Center / Curved with Flat Tip Combination

Combinación centro rebajado/curva con punta plana

Combinaison base creuse / courbe avec embout plat

Model	Item No.	Length	Stock	Weight
T2122Z18	31835	18" (46 cm)	9/16" (14 mm)	1.3 lbs (.6 kg)
T2122Y18	31845	18" (46 cm)	5/8" (16 mm)	1.6 lbs (.7 kg)
T2122X18	31855	18" (46 cm)	11/16" (17.5 mm)	1.8 lbs (.8 kg)
T2122Z24	32435	24" (61 cm)	9/16" (14 mm)	1.7 lbs (.8 kg)
T2122Y24	32445	24" (61 cm)	5/8" (16 mm)	2.1 lbs (1 kg)
T2122F24	32455	24" (61 cm)	11/16" (17.5 mm)	2.5 lbs (1.1 kg)
T2122A30	33055	30" (76 cm)	11/16" (17.5 mm)	3.1 lbs. (1.4 kg)
T2122M30	33065	30" (76 cm)	3/4" (19 mm)	3.4 lbs (1.5 kg)

Small Tire Mount/Demount Irons

Barras para montaje/desmontaje de llantas pequeñas

Leviers de montage/démontage de petits pneus



New designs are based on popular European styles. Extended length of the flat curved sliding surface provides mounting ability comparable to much longer traditional tire irons. Sizes available for motorcycle, passenger, truck, and heavy-duty tires. Designed for mounting and demounting tires. Best if used in pairs.



Motorcycle / Small Wheel

Ruedas pequeñas/de motocicleta

Motocyclette / Petites roues



Model	Item No.	Length	Stock	Weight
T43A	39805	15" (38 cm)	3/4" (19 mm)	1.8 lbs (.8 kg)

Mount / Demount Tire Tools - Small Tire

Herramientas para montaje y desmontaje de llantas - Llantas pequeñas

Outils de montage/démontage de pneus - Petits pneus



Tools are used in pairs to mount or demount small passenger, industrial, ATV, and motorcycle tires.



Model	Item No.	Length	Stock	Weight
T6A	32106	16-1/2" (42 cm)	5/8" (16 mm)	1.5 lbs (.7 kg)

Tire Irons - Small Tire

Barras para llantas - Llantas pequeñas
Démonte-pneus - Petits pneus



Pro tire changing tools for small tires. Ideal for mounting and demounting motorcycle, ATV, lawn tractor, golf cart, and small tires by hand. Rounded ends will not pinch tube. Patented.

Model	Item No.	Length	Stock	Weight
T9A	32109	9" (23 cm)	7/16" (11 mm)	.4 lbs (.16 kg)
T16A	32116	16" (41 cm)	7/16" (11 mm)	.7 lbs (.3 kg)
T9C	32110	2 pc. Carded Set - Contains: Qty. (2) T9A 9" Bars		
T16C	32117	2 pc. Carded Set - Contains: Qty. (2) T16A 16" Bars		

Tire Irons - Small Tire

Barras para llantas - Llantas pequeñas
Démonte-pneus - Petits pneus



Pro tire changing tools for small tires. Sturdy, comfortable plastic handles. Ideal for mounting and demounting motorcycle, ATV, lawn tractor, golf cart, and small tires by hand. Rounded ends will not pinch tube.

Model	Item No.	Length	Stock	Weight
T5	32115	16" (41 cm)	7/16" (11 mm)	.8 lbs (.36 kg)
T8	32118	16" (41 cm)	7/16" (11 mm)	.8 lbs (.36 kg)
32114	32114	2 Pc. Small Tire Iron Set Contains: Qty. (1) T5 (32115) Qty. (1) T8 (32118)		

European Style Tools

Herramientas de estilo europeo
Outils de style européen



Use on car, motorcycle, truck, and agricultural tires. Designed for mounting and demounting tires.

Best if used in pairs.



Model	Item No.	Length	Stock	Weight
T43C	39806	21" (53 cm)	7/8" (22 mm)	3.1 lbs (1.4 kg)




Model	Item No.	Length	Stock	Weight
T43D	39810	30" (76 cm)	7/8" (22 mm)	4.5 lbs (2.0 kg)



Model	Item No.	Length	Stock	Weight
T44	39808	31" (79 cm)	7/8" (22 mm)	5.3 lbs (2.4 kg)

T44 illustration



Cross Reference:

Ken-Tool No.	T43A	T43C	T43D	T44	T45SX	T45DX	T41
CPM	Livraison Ref. 1547	Face 68 Ref.426/68	Force Ref. 1289	Halte Ref. 1060	Hyoca Ref. 1194	Hyude Ref. 1195	Sayam Ref. 858

Tire Mount / Demount Spoons

Espátula para montaje/desmontaje de llantas
Cuillères de montage/démontage de pneus

These tools are designed for fast and efficient tire changing. Use the 18" and 24" spoons to mount or demount passenger car, motorcycle, ATV, and light truck tires. The 30" spoons provide enough strength and leverage to work on large truck, bus, off-road vehicle, tractor, and aircraft tires.



Straight • Recta • Droite

Model	Item No.	Length	Stock	Weight
T1X	32101	18" (46 cm)	11/16" (17.5 mm)	1.8 lbs (.8 kg)
T19	32119	24" (61 cm)	11/16" (17.5 mm)	2.5 lbs (1.1 kg)
T19A	33219	30" (76 cm)	11/16" (17.5 mm)	3 lbs (1.4 kg)
T19M	33022	30" (76 cm)	3/4" (19 mm)	3.4 lbs (1.54 kg)
T38	33238	30" (76 cm)	7/8" (22 mm)	4.8 lbs (2.2 kg)

Drop-Center

Combinación con base con caída • Base creuse

Model	Item No.	Length	Stock	Weight
T21R	32121	18" (46 cm)	11/16" (17.5 mm)	1.8 lbs (.8 kg)
T21F	34121	24" (61 cm)	11/16" (17.5 mm)	2.5 lbs (1.1 kg)
T21HD	34122	30" (76 cm)	7/8" (22 mm)	4.5 lbs (2.0 kg)

Curved • Curva • Courbe


Model	Item No.	Length	Stock	Weight
T2X	32102	18" (46 cm)	11/16" (17.5 mm)	1.8 lbs (.8 kg)
T20	32120	24" (61 cm)	11/16" (17.5 mm)	2.4 lbs (1.1 kg)
T20A	33220	30" (76 cm)	11/16" (17.5 mm)	3.1 lbs (1.4 kg)
T20M	33023	30" (76 cm)	3/4" (19 mm)	3.4 lbs (1.54 kg)
T39	33239	30" (76 cm)	7/8" (22 mm)	4.5 lbs (2.0 kg)

Lock Ring Tools

Herramientas para anillos de seguridad

Outils pour anneau verrouilleur

These tools are designed to remove most truck lock rings. A must-have for anyone mounting or demounting multi-piece rims. Use in pairs.



Truck Lock Ring Remover

Desmontador para anillos de seguridad para camiones

Dégageur d'anneau verrouilleur pour camions



Designed for smaller diameter wheels.



Model	Item No.	Length	Stock	Weight
T23 [®]	32123	24" (61 cm)	11/16" (17.5 mm)	2.4 lbs (1 kg)

Truck Lock Ring Remover

Desmontador para anillos de seguridad para camiones

Dégageur d'anneau verrouilleur pour camions



Designed for smaller diameter wheels.



Model	Item No.	Length	Stock	Weight
T23A [®]	33223	30" (76 cm)	11/16" (17.5 mm)	3.1 lbs (1.4 kg)

Combination Rim / Ring Tool

Herramienta para combinación de llantas/anillos

Deux en un pour jante/anneau



Flat tapered end ideal for all around ring and rim work.



Model	Item No.	Length	Stock	Weight
T23B	33224	23-1/2" (60 cm)	11/16" (17.5 mm)	2.4 lbs (1 kg)

Rim Lock Tool

Herramienta para anillos de seguridad de llantas

Bloque-talons



For servicing wide base rims.



Model	Item No.	Length	Stock	Weight
T25	32125	18" (46 cm)	11/16" (17.5 mm)	1.8 lbs (.8 kg)

Special Lock Ring Tool

Herramienta para anillos de seguridad especiales

Outil spécial pour anneau verrouilleur



Long tapered curved end for continuous side rings.



Model	Item No.	Length	Stock	Weight
T27	32127	18" (46 cm)	11/16" (17.5 mm)	1.8 lbs (.8 kg)

Lock Ring Tool

Herramienta para anillos de seguridad

Outil pour anneau verrouilleur



Removes continuous side rings on two-piece truck rims.



Model	Item No.	Length	Stock	Weight
T27A	32128	18" (46 cm)	11/16" (17.5 mm)	1.8 lbs (.8 kg)

Heavy-Duty Lock Ring Tool

Herramienta para anillos de seguridad de alta resistencia

Outil robuste pour anneau verrouilleur



Use for multi-piece wheels, especially hub type.

Model	Item No.	Length	Stock	Weight
T48A	34648	37" (94 cm)	3/4" (19 mm)	4.6 lbs (2.1 kg)

Industrial Wheel Lock Ring Set

Juego de anillos de traba para ruedas industriales

Jeu d'anneaux verrouilleurs de roues industrielles


32131
Demount
Prep Tool



Separator end separates split ring from solid flange ring

Pry-out end reaches behind slotted end of split ring to pry it out and over the flange of the wheel

32130
Mount /
Demount
Tool



Demount end lifts and fully demounts split ring

Mount end is used to mount split ring

Specially designed to remove & replace lock rings on multi-piece industrial forklift wheels. Removing and replacing lock rings on multi-piece industrial wheels presents its own set of unique problems – these tools are specifically designed to make that job easier, faster, and safer. Helps prevent injury – easier to keep hands safely outside of press cage! Powder coated to protect from rust and corrosion; bright orange color helps prevent lost tools. Forged from high-grade carbon steel and heat-treated for long-lasting strength and durability. Patented.

Set No. 32129 Weight: 3.3 Lbs (1.5 kg). Patented.

2 Pc. Set Includes:

Model	Description	Length	Stock	Weight
32130	Mount Demount Tool	15-3/4" (40 cm)	3/4" (19 mm)	1.8 lbs (.8 kg)
32131	Demount Prep Tool	15-1/2" (40 cm)	3/4" (19 mm)	1.5 lbs (.7 kg)



Industrial Wheel
Lock Ring Tool
Set #32129

DON'T RISK INJURY



IRONMAN™

Ergonomic Wheel Lifting Bar

Barra ergonómica para el levantamiento de neumáticos Ironman™

Barre ergonomique de levée de roue Ironman™




IronMan™
Wheel Lifting Bar

ERGONOMIC:
Use the leverage
created by the tool
– **NOT YOUR BACK!**

Reduces back strain. Easily and safely lift heavy, awkward truck tire and wheel assemblies. Extremely useful in outdoor conditions – when truck tire and wheel assemblies can become wet and slippery. Lift all sizes and types of small and large heavy truck wheels: Standard sizes including 22.5" and 24.5" wheels, plus European (which have 1" lug holes), Super Wide and even the Super Single (a 340 lb. assembly) size.



Specially designed forged ends work from either side of the wheel assembly as it lays flat



Specially designed forged knob end for hub side up

Specially designed spoon end for hub side down

Model	EDP No.	Length	Stock	Weight
34950	T950	58" (147 cm)	1" (25 mm)	10 lbs (4.5 kg)

Aluminum Wheel Protector

Protector de cubiertas de aluminio
Protecteur pour roues en aluminium



Protect expensive rims from damage during manual tire changing. Prevents tire tools from marring or scratching aluminum or steel rims when using Ken-Tool's manual tire changing tools. Durable leather protector fits on the rim and protects inside of the rim well. Use with an assortment of tire tools including: T45A® - style tire irons, Serpent™, tire spoons, other Ken-Tool tire changing tools. When one end wears out, flip it over and use the opposite end. Great for roadside service or in the shop. Patented.

Model	Item No.	Description	Weight
31810	31810	Leather	.35 lbs (.15 kg)

Bead Holding Devices

Dispositivos de fijación de talón

Dispositifs de retenue des talons

Bead Holding Device

Dispositivo para soporte de llantas

Dispositif de retenue des talons



Now reaches over extra wide bead of super singles. Holds the bead in place against the wheel when mounting the tire on to the wheel. Do not use to pry. **Imported.**

Model	Item No.	Description	Weight
31710	31710	Solid Brass	1.8 lbs (.8 kg)



Bead Holding Device



How to Properly Use Bead Holders #31710 on a 21L-24 Backhoe Tire and Wheel

Aluminum Bead Holder For Steel & Aluminum Wheels

Sujetador de talón de aluminio para ruedas de acero y aluminio

Support de talon en aluminium pour roues en acier et en aluminium



Part No.
31713

Part No.
31714



Special C-Lok™ shape fits nearly all passenger, light truck, agriculture and truck wheels without slipping off. Patent pending aluminum design is lightweight but very strong and is less likely to mar alloy wheels. Great for super singles and super wide wheels — fits both steel and aluminum wheels. Available as a cabled pair No. 31714 for difficult wheels. Patented. **Imported.**



Newest Bead Holder - Made From Aluminum



Aluminum Bead Holder

Model	Item No.	Description	Weight
31713	31713	Single Aluminum Bead Holder	0.5 lb (.22 kg)
31714	31714	32" Cabled Pair	1 lb (.5 kg)

Bead Holder For 19.5" Aluminum Wheels

Sujetador de talón para ruedas de acero y aluminio de 19.5"

Support de talon pour roues en aluminium de 19,5 po



Steel bead holder for 19.5" aluminum truck wheels that fit 9/16" diameter studs. Always mount/demount 19.5" wheels with hub side up. Patented.

Model	Item No.	Description	Weight
33196	33196	Bead Holder for 19.5" Aluminum Wheels	1 lb (.5 kg)

Bead-Breaking Tools Truck / Farm / OTR

Herramientas desmontadoras de llantas para camiones/vehículos de granja/de carretera

Outils de décollage des talons pour camions/tracteurs/véhicules tout terrain



These lightweight, portable tools are a great alternative to handled bead breaking wedges or hydraulic bead breakers. One end is used to remove frozen or rusted beads from all types of rims. On the T52, the other end can be used as a leverage bar when inserted into the 35695 or 35697 Truck Lug Wrench.

Swan Neck Leverage Bar

Palanca de cuello de cisne

Barre de levage à col de cygne



Model	Item No.	Length	Stock	Weight
T41	33341	30" (76 cm)	7/8" (22 mm)	5.3 lbs (2.4 kg)

30" Bead Breaker

Desmontadora de llantas de 30 pulgadas

Démonte-talons de 30 po



Model	Item No.	Length	Stock	Weight
T42	33342	30" (76 cm)	7/8" (22 mm)	4.8 lbs (2.2 kg)

Bead Breaker Leverage Bar

Palanca desmontadora de llantas

Barre de levage pour démonte-talons



Also for use with the T95 wrenches.

Model	Item No.	Length	Stock	Weight
T52	34652	33" (84 cm)	7/8" (22 mm)	5.5 lbs (2.5 kg)

Portable Bead Breaker

Desmontadora de llantas portátil

Démonte-talons portatif



Portable bead-breakers are great for custom and foreign wheels. They break beads on most sizes of passenger tires and light trucks.

Model	Item No.	Handle Length	Weight
T100	34670	36" (91 cm)	5.2 lbs (2.3 kg)

Bead-Breaking Tool / Driving Iron

Herramienta desmontadora de llantas/barra de hierro desmontadora

Outil de décollage des talons/Levier d'entraînement



Driving iron is used for loosening rusted truck and bus beads. Will speed truck tire repair work and save labor and time.


Model	Item No.	Length	Stock	Weight
T26A	32126	11-3/4" (30 cm)	1-1/4" (32 mm)	4.4 lbs (2 kg)

Impact Bead Breakers

Desmontadoras de llantas de impacto

Démonte-talons à chocs

Bead breaker loosens beads with bead-breaking foot and ram bar, but never cuts the bead of the tire. The wedge foot is forced between the bead and rim flange. Breaker is designed for shop or road use. No other bead breaking tools are necessary. Provides greater accuracy than other conventional bead breakers.



T24B



T26B

T26B has exclusive spring action design to reduce user fatigue associated with slide hammer kickback.

Model	Item No.	Description	Length	Length Extended	Weight
T24B	35924	Economy	46" (117 cm)	72" (183 cm)	13.5 lbs (6.1 kg)
T26B	35926	Heavy-duty	50" (127 cm)	80" (203 cm)	23 lbs (10.4 kg)

Floor Type Bead Breakers

Desmontadoras de llantas con pie

Démonte-talons sur sol



Ideal for stubborn tires. Use to prevent the bending of wheels. A great solution for custom and foreign wheels.



Model	Item No.	Description	Tread Width	Weight
T98	35998	Deluxe	up to 11" (28 cm)	29.8 lbs (13.5 kg)

Valve Breaker™

Herramienta para romper válvulas Valve Breaker™
Outil casse-valve Valve Breaker™



Valve Breaker Tool™:
How To Use It

Part No.
35934

Part No.
35936

PATENTED

Solid ram bar (not hollow pipe)
drives more energy into valve

Repair Kit
Part No. 35935

Quickly & easily remove valve stems from wheels! Made in USA from quality, high-grade steel. Heat-treated punch for top performance and long life. Pinch-preventing Safety Grip with vibration dampening tube grip. Long-lasting baked powder coat finish. T34B designed to fit into most 30" toolboxes. Simple to re-build — only 3 components. Patented.

Model	Item No	Description	Length	Weight
35934	T34B	Valve Breaker	27"	9 lbs (4.1 kg)
35936	T36B	Valve Breaker	45"	16 lbs (7.2 kg)
35935	35935	3 pc. Repair Kit	Bagged	1 lb (.5 kg)

Duck-Billed Bead Breaking Wedges

Our most popular bead breakers.
Cuñas desmontadoras de
llantas de boca plana
Coins d'écartement de
talons en bec de canard




Wood Handled

Con mango de madera
Manche en bois



Increased contact area between the handle and the hammer head causes the handle to have a tighter fit when the head is seated on the handle. By increasing end-taper of the handle the hammer head cannot come off the end of the handle. No slits in the top of the handle minimizes the effect of Humidity/Climate (expansion & contraction) on the handle.




Model	Item No.	Handle No.	Length	Weight
T11D	35327	T11DH	17" (43 cm)	4.8 lbs (2.2 kg)
T11E®	35329	T11EH	30" (76 cm)	11 lbs (5 kg)

New T11ES orange safety grip handle. Specially formulated granulated handle coating provides extra grip for sure control of the steel bead breaking wedge

Model	Item No.	Handle No.	Length	Weight
NEW T11ES	35330	T11EHS	30" (76 cm)	11 lbs (5 kg)

Fiberglass Handled


Con mango de fibra de vidrio
Manche en fibre de verre



Model	Item No.	Handle No.	Length	Weight
TG11D	35427	TG11DH	18" (46 cm)	4.8 lbs (2.2 kg)
TG11E	35429	TG11EH	32" (81 cm)	11 lbs (5 kg)

Polymer Handled

Con mango de polímero
Manche en polymère



PATENTED



Handle
cross section



Hump Design prevents tool from wedging between rim and bead. Breaks the bead with little or no prying. New polymer handle design for longer lasting everyday use. Full length fiberglass core for greater strength. Coating on handle provides durability.

Model	Item No.	Replacement Handle	Length	Head Weight
T11K™	35460	T11KH (35230)*	32" (81 cm)	10.5 lbs (4.8 kg)

*New handle design T11KH (35230) will not work with old style T11E head

For more information visit us at www.kentool.com



General Purpose Tire Hammers • Martillos para llantas universales • Masse à tout usage

Designed for tire service in a variety of sizes and styles. Use rubber head replacement T11RH (35104).


Wood Handled

Con mango de madera

Manche en bois

Model	Item No.	Handle No.	Length	Weight
T11B	35311	T11BH	14-1/2" (37 cm)	4.5 lbs (2.0 kg)

Model	Item No.	Handle No.	Length	Weight
T33R	35317	T11HN	14" (36 cm)	2.3 lbs (1.0 kg)




Fiberglass Handled

Con mango de fibra de vidrio

Manche en fibre de verre

Model	Item No.	Handle No.	Length	Weight
TG11B	35411	TG11BH	16" (41 cm)	4.8 lbs (2.1 kg)

Model	Item No.	Handle No.	Length	Weight
TG33R	35417	TG31H	16" (41 cm)	2.5 lbs (1.1 kg)



Heavy Duty Tire Hammers • Martillos para llantas de alta resistencia • Masses à pneu robuste

Hammers are used for mounting and demounting tires. They make tire changing faster and easier for passenger car, truck, bus, farm tractor, and aircraft tires. A variety of weights and sizes are offered to meet all your tire changing needs. Non-marring rubber end can be used for driving on lock rings. Use rubber head replacement T34RH (35105).

Wood Handled

Con mango de madera

Manche en bois

Model	Item No.	Handle No.	Length	Head Weight	Weight
T34	35321	T11CH	17" 43 cm	4.8 lbs 2.2 kg	5.4 lbs 2.4 kg

Model	Item No.	Handle No.	Length	Head Weight	Weight
T35	35323	T11CH	16-1/2" 42 cm	5.5 lbs 2.5 kg	6.1 lbs 2.7 kg

Model	Item No.	Handle No.	Length	Head Weight	Weight
T36	35325	T11CH	16-1/2" 42 cm	5.8 lbs 2.6 kg	5.3 lbs 2.4 kg



Fiberglass Handled

Con mango de fibra de vidrio

Manche en fibre de verre

Model	Item No.	Handle No.	Length	Head Weight	Weight
TG34	35421	TG11CH	18" 46 cm	5.5 lbs 2.5 kg	6 lbs 2.7 kg

Model	Item No.	Handle No.	Length	Head Weight	Weight
TG35	35423	TG11CH	18" 46 cm	4.8 lbs 2.2 kg	6.6 lbs 3.0 kg

Model	Item No.	Handle No.	Length	Head Weight	Weight
TG36	35425	TG11CH	18" 46 cm	5.8 lbs 2.6 kg	6 lbs 2.7 kg



Replacement Handles

Mangos de repuesto

Manches de remplacement

Top Quality U.S. Hickory

U.S. Hickory de máxima calidad • Qualité supérieur U.S Hickory

T11EHS

New T11EHS orange safety grip handle. Specially formulated granulated handle coating provides extra grip for sure control of the steel bead breaking wedge

T11EH

Model	Item No.	For Hammer No.	Length	Weight
T11BH	35111	T11B	15" (38 cm)	.75 lbs (.3 kg)
T11HN	35113	T11R, T31, T33R	15" (38 cm)	.75 lbs (.2 kg)
T11CH	35119	T11C, T34, T35, T36	17" (43 cm)	.75 lbs (.3 kg)
T11DH	35127	T11D	17" (43 cm)	.75 lbs (.3 kg)
T11EH	35129	T11E®	30" (76 cm)	1.2 lbs (.5 kg)
T11EHS	35131	T11E®	30" (76 cm)	1.2 lbs (.5 kg)
80H-3H	37012	80H-3, 80H-4	10" (25 cm)	.5 lbs (.2 kg) NEW
85H-3H	37023	85H-3, 84H-2, 84H-4	15" (38 cm)	.75 lbs (.3 kg) NEW
84H-8H	37025	84H-8, 84H-10, 84H-12, 84H-16	36" (91 cm)	1.4 lbs (.6 kg) NEW
84H-20H	37089	84H-20	36" (91 cm)	1.4 lbs (.6 kg) NEW

Aluminum • Aluminio • Aluminium

Model	Item No.	For Hammer No.	Length	Weight
T11AH	35529	T11E®, TG11E	32" (81 cm)	4.3 lbs (2 kg)

Polymer • Polímero • Polymère Patented

Model	Item No.	For Hammer No.	Length	Weight
T11KH	35230	T11K™	32" (81 cm)	2.3 lbs (1.0 kg)

Fiberglass • Fibra de vidrio • Fibre de verre

Model	Item No.	For Hammer No.	Length	Weight
TG37H				
TG31H	35206	TG11R, TG31, TG33R	16" (41 cm)	1 lb (.5 kg)
TG11BH	35211	TG11B	16" (41 cm)	1.3 lbs (.6 kg)
TG11CH	35219	TG11C, TG34, TG35, TG36	18" (46 cm)	2.5 lbs (1.1 kg)
TG11DH	35227*	TG11D	18" (46 cm)	1.2 lbs (.5 kg)
TG11EH	35229*	TG11E	32" (81 cm)	2.3 lbs (1.0 kg)

* Nulok adapter (others use epoxy).

Replacement Rubber Heads

Cabezas de goma de repuesto

Tête de remplacement en caoutchouc

Model	Item No.	Description	For Hammer No.
T11RH	35104	Rubber Head	T11R, TG11R, T33R, TG31
T34RH	35105	Rubber Head	T34, TG34, T35, TG35, T36, TG36

Epoxy Kits • Equipos de epoxy • Ensembles en époxy

Model	Item No.	Description	For Hammer No.
T12B	35201	Epoxy Kit	TG11B, TG11R, TG31, TG33R
T12D	35202	Epoxy Kit	TG34, TG35, TG36, TG37

Tire Snake®

'Snake®' para llantas / 'Snake®' Outil à pneu
Snake®

Tire Snake mounting and demounting tools for use with center post tire changers. Included with T600 Tire Changer, designed for wheels from 4" to 12". Included with T601 Tire Changer, designed for wheels from 4" to 15", the longer length provides greater leverage. Patented.



Model	Item No.	Length	Stock	Weight
TS72	34672	22" (56 cm)	5/8" (2 cm)	2 lbs (.9 kg)
TS74	34674	28" (71 cm)	5/8" (2 cm)	2.5 lbs (1.1 kg)
TS42	34678	42" (102 cm)	3/4" (19 mm)	5.3 lbs (2.4 kg)

Air Blast Bead Seater for Small Tires

Calzador a chorro de aire para llantas pequeñas

Air comprimé pour repos de talon de petits pneus



For your small tire changing needs, Ken-Tool introduces a fast, easy and economical way to seat beads in one simple operation with the new Air Blast Bead Seater. This patent-pending air-blaster bead seater, seats the bead on most small tubeless tires with rims ranging from 4 to 12 inches. This is a one-man operation; just point, release, and watch this fast-acting bead seater do all the work.

Model	Item No.	Weight
31440	31440	5.6 lbs (2.5 kg)

ATV Bead Breaker
Desmontadora de llantas
para vehículos todo terreno
Décolleur de talon
pour VTT



The ATV Bead Breaker is a manual solution that satisfies both manufacturers and tire changing technicians searching for a quick, safe, and affordable ATV bead breaker that really works. A rugged, yet lightweight tool that delivers the tremendous force necessary to overcome the resistance of a bead keeper. Constructed of heavy-duty steel, the ATV Bead Breaker works with any center post tire changing machine and adjusts to sizes of 6 to 12 inch ATV rims without the hassle of clevis pins. No hammers, wrenches, or additional tools are required. Very affordable! Patented.

Model	Item No.	Weight
38620	38620	7 lbs (3.2 kg)

Manual Tire Changers

Cambiadores de llantas manuales

Démonteurs de pneus manuels



Floor Mount

Montaje de piso

Montage au sol



Threadscrew
has been
milled to fit
MTD wheels.



Mounts and demounts a full range of tires on rim diameters from 4 to 15 inches. Tapered bearing guide positively centers straight shaft hubs of all diameters. A built-in, infinitely adjustable bead breaker works on rims up to 15" in diameter and 24" in width without disassembly. Includes a Ken-Tool exclusive, 28" Tire Snake® mount/demount tire tool. Patented.

Model	Item No.	Height	Weight
T601	38601	32" (81 cm)	31 lbs (14 kg)





Small Tire
Changing Tools
Part 1

Bench / Rim Clamp Mount

Montaje de banco/
abrazadera de llantas

Montage sur
banc/crapaud



Threadscrew
has been
milled to fit
MTD wheels.



Mounts and demounts a full range of tires on rim diameters from 4 to 12 inches. Mounts easily to a bench or in any standard, four-position rim-clamp tire changer. A built-in, three fin centering device mounts standard lug-type rims with 2" and larger center hole. Square base prevents turning in the changer during use. Includes a Ken-Tool exclusive, 22" Tire Snake® mount/demount tire tool. Patented.

Model	Item No.	Height	Weight
T600	38600	16-1/2" (42 cm)	21.7 lbs (10 kg)

For additional small tire tools see page 16

Tire Mount / Demount Lubricants

Lubricantes para montaje/desmontaje de neumáticos

Lubrifiants de montage & démontage de pneus



Professional grade lubricants make tire mounting and demounting easier and more efficient.

Tiger Paste Lubricant

Lubricante Tiger Paste
Lubrifiant Tiger Paste

Superior formulation for commercial, OTR and specialty equipment tires, with rust inhibitor.

Model	Item No.	Weight
35837	35837	7.5 lb. (3.4 kg)



Ultra Lube

Lubricante Ultra Lube
Lubrifiant Ultra Lube

Premium rim and rust retardant and tire mounting lubricant for demanding applications.

Model	Item No.	Weight
35839	35839	25 lb. (11.4 kg)



Euro Paste Lube

Lubricante Euro Paste Lube
Lubrifiant Euro Paste Lube

Premium tire mounting lubricant dries tacky to prevent rim lippage, with rust retardant.

Model	Item No.	Weight
35848	35848	8 lb. (3.6 kg)



Heavy Paste Lube

Lubricante Heavy Paste Lube
Lubrifiant Heavy Paste Lube

Concentrated economical tire mounting and bead packing lubricant, makes up to 15-gallons.

Model	Item No.	Weight
35840	85840	25 lb. (11.4 kg)



Bead-Eze® Tire Lubricant

Lubricante para neumáticos Bead-Eze®
Lubrifiant de pneu Bead-Eze®

Penetrating water-based lubricant for tire mounting, can be diluted for leak detection, six-pack.

Model	Item No.	Description	Weight
35847	85847	One Gallon, 6-Pack	54 lbs (24.5 kg)



Bead-Eze® Tire Lubricant

Lubricante para neumáticos Bead-Eze®
Lubrifiant de pneu Bead-Eze®

Penetrating water-based lubricant for tire mounting, can be diluted for leak detection.

Model	Item No.	Description	Weight
35847S	85847S	One Gallon, single	9 lb. (4.1 kg)



Detecto Mist® Leak Locator

Localizador de fugas Detecto Mist®
Localisateur de fuites Detecto Mist®

Spray on tire to instantly detect air leaks, concentrated formula dilutes with water.

Model	Item No.	Description	Weight
35805	85805	One Quart	2.3 lb. (1 kg)



Lubricant Applicators

Aplicadores de lubricantes
Applicateurs de lubrifiant

Bead Lubricant Swab

Estropajo para lubricante de talones
Écouvillon pour lubrifiant de talon

Durable cotton applicator quickly holds and applies lube, twisted wire construction and wood handle.



NEW Euro Style Lube Brush

Pincel para lubricante estilo europeo
Brosse de lubrification style européen

Designed to the ideal angle to fit between the tire bead and rim. Imported.



Model	Item No.	Length	Weight
NEW 30512	30512	11" (27.9 cm)	10 oz (.3 kg)

OSHA Tire Service Charts

Cuadros de servicio de neumáticos OSHA
Diagrammes d'entretien des pneus OSHA




OSHA Tire Mount/Demount Safety Instructions & Charts. 24" x 70" High Quality posters. Suitable for wall mounting in service area per OSHA 29 CFR 1910.77.

Includes:

Demounting & Mounting Procedures for Tube-type Truck & Bus Tires Chart (OSHA 3402 10R-11)

Demounting & Mounting Procedures for Tubeless Truck & Bus Tires Chart (OSHA 3401 10R-11)

Multi-Piece Rim Matching Chart (OSHA 3403 10R-11)



Model	Item No.	Description	Weight
39998	39998	3 Poster Set	1 lb (.5 kg)

Tire Bead Seaters

Calzador para llantas

Cordons de talon de pneus

One-piece rubber tube for mounting hard-to-seat radial, bias-belted, or conventional truck tires. As tire is inflated, the lubricated bead seater forms a seal between the rim and tire, allowing the air pressure to force the beads into the rim flange. As proper pressure is reached, the bead seater slides out and over the rim. Use bead lubricant with bead seaters.



Passenger / Light Truck

Camión liviana/vehículo de pasajeros • Automobile/camion léger

Model	Fits Rim Sizes	Weight
31446	14-15" (36 - 38 cm)	1.5 lbs (.7 kg)

Truck • Camión • Camion

Model	Fits Rim Sizes	Weight
31437	16-1/2" to 17-1/2" (42 to 45 cm)	2 lbs (.9 kg)
31438	19-1/2" (50 cm)	2.3 lbs (1 kg)
31439	22-1/2" to 24-1/2" (57 to 62 cm)	2.3 lbs (1 kg)

Pneumatic Bead Expanders

Expansores neumáticos de llantas

Tubes d'extension de talon pneumatiques



Expanders fit most bias ply tubeless tires. A pliable neoprene rubber tube is encased in a tough, long-lasting nylon cover. Expanders slip easily over tire and withstand contact with oil, grease, solvents, and acids. Expands bead by compressing tread to seat beads. **T131** is for smaller tires, **T132** for belted bias ply tires and steel belted radials, and **T133** for standard bias ply tires. All models feature an over-pressure relief valve and external pressure quick release valve for safe operation.

Model	Item No.	Min / Max Diameter	Tube Diameter	Weight
NEW T131	31431	10 - 22" (26 - 56 cm)	2-1/4" (6 cm)	2 lbs (.9 kg)
T132	31432	24 - 34" (61 - 86 cm)	2-1/4" (6 cm)	2.8 lbs (1.2 kg)
T133	31433	22 - 32" (60 - 81 cm)	3/4" (2 cm)	.75 lbs (.3 kg)

"Challenger" Wheel Balancer

Balanceador de ruedas • Équilibreuse de roues

Accurate, easy-to-operate, self-leveling balancer with easy-to-read circular level accurately balances all wheels when using regular weights. Bubble type balancer is portable and may be used indoors or outdoors, even on a stone driveway. Convenient built-in weight storage space in the base of the balancer combines everything needed in 2 sq. ft. of floor space. All steel parts are plated to resist rust. Most passenger car wheels can be balanced directly on the balancer. Bubble will not freeze. Restriction: Minimum 1-1/2" diameter hub holes to maximum 4-1/2" hub holes. **Imported.**



Model	Item No.	Description	Size	Weight
X161	31361	Wheel Balancer	22"H x 12"W x 12"L	14 lbs (6.4 kg)
X-161-1	31361-01	Balance Head		5.3 lbs (2.4 kg)
X-161-99	31361-99	Bubble Device		.75 lbs (.3 kg)

Wire Brush

Cepillo de alambre • Brosse métallique

Cleans rust from rims and wheels.



Model	Item No.	Length	Weight
T15	30515	14" (36 cm)	5 oz. (.2 kg)


Tire Spreaders

Separadores de llantas • Écarte-pneus

Tire Spreader with Lock Pin

Separador de llanta con pasador de bloqueo

Écarte-pneu avec goupille de sécurité



Imported.




Model	Item No.	Spread Capacity	Weight
T51	31551	4" - 6" (10-15 cm)	3.9 lbs (1.7 kg)

Ratchet Action Truck Tire Spreader

Separador de llantas para camiones

Ratchet Action

Écarte-pneu à rochet pour camions



Model	Item No.	Spread Capacity	Weight
T54	31554	3-1/2" - 14" (9 - 36 cm)	7.3 lbs (3.3 kg)

Professional Wheel Weight Tool

Herramientas profesional para pesar ruedas

Outil professionnel pour masses d'équilibrage

Clip-claw crowbar, punch designed handles, and heavy hammerhead provide years of use. **Imported.**

Model	Item No.	Weight
B230	35354	1 lb (.5 kg)



Standard Wheel Weight Tool

Herramientas estándar para pesar ruedas

Outil standard pour masses d'équilibrage

This passenger car wheel weight tool is the industry standard. **Imported.**

Model	Item No.	Weight
B232	35355	1 lb (.5 kg)



Professional 4-Way Valve Core Tool

Herramienta profesional para núcleos de válvulas de 4 vías

Outil à valve professionnel 4 en 1 pour noyaux

Handy 4-in-1 standard valve tool repairs cap threads, repairs core threads, has special easy-out feature for removing damaged cores, and screwdriver for removing standard cores. Black, heavy-duty hardened steel. **Imported.**

Model	Item No.	Weight
T16P	30215	1 oz (.04 kg)



Cap Nut Wrenches

Llaves de tuercas ciegas

Clés à écrou borgne

Ken-Tool Porkchop™



Wrenches hold outer cap nut on dual wheels while the inner nut is turned. Lip fits in hole to secure wrench in place. Sizes offered fit standard and metric cap nuts.

Model	Item No.	Description	Size	Weight
TX9®	30609	SAE	1-1/2"	.73 lbs (.3 kg)
TX10	30610	Metric	35 mm	.4 lbs (.1 kg)
TX12	30612	Metric	41 mm	.4 lbs (.1 kg)

Combination Cap Nut Wrench

Llave de tuercas ciegas de combinación

Clé à écrou borgne deux en un



Offers the versatility of two wrenches in one unique product design. Fit one end onto the outer cap nut with the other end through the center hole. Wrench slides underneath center disc of wheel, reducing slipping during nut removal.



Combination
Cap Nut
Wrench

Model	Item No.	Description	Size	Weight
TX50	30620	SAE & Metric	41 mm, 1-1/2"	1.3 lbs (1 kg)

Heavy-Duty Cap Nut Wrenches

Llaves de tuercas ciegas de alta resistencia

Clés robustes à écrou borgne



PATENTED



Heavy-duty design will not slip out of position. Wrench rests snugly against the center hole, reducing the possibility of rim damage. Ideal for aluminum wheels.



Heavy-Duty
Cap Nut
Wrenches

Model	Item No.	Description	Size	Weight
TX200	30618	SAE	1-1/2"	2.6 lbs (1.2 kg)
TX241	30619	Metric	41 mm	2.6 lbs (1.2 kg)

Professional Lug Nut Cover Remover

Desmontador profesional de cubierta con tuercas

Dégageur professionnel d'écrous d'enjoliveurs de roues

Special coating will not scratch or damage chrome, painted, or coated lug nut covers.

Model	Item No.	Weight
30606	30606	1.3 lbs (.6 kg)



Wheel Cover Puller / Replacers

Extractor/cambiadores de cubiertas

Extracteur de garde-roues/garde-roues d'échange

Removes wheel covers quickly and easily without gouging or scratching them. Rubber head **T11RH** prevents damage to hub cap and is replaceable.



Pro
Profesional
Professionnel



Model	Item No.	Length	Stock	Weight
T67	31567	17-1/2" (45 cm)	9/16" (14.3 mm)	1.8 lbs (.8 kg)

Standard
Estándar
Standard



Model	Item No.	Length	Stock	Weight
T68®	31568	14" (36 cm)	7/16" (11.1 mm)	1.3 lbs (.6 kg)

Center Cap Removers

Desmontadores de tapas centrales

Extracteur de chapeau centrale

Wide Blade
Paleta ancha
Lame large



Removes larger center covers without damaging wheels.

Model	Item No.	Length	Stock	Weight
T65	31565	7-3/4" (19.6 cm)	5/16" (7.9 mm)	.2 lbs (.09 kg)

Narrow Blade
Paleta angosta
Lame étroite



Removes small delicate center covers without wheel damage.

Model	Item No.	Length	Stock	Weight
T66	31566	7-3/4" (19.6 cm)	5/16" (7.9 mm)	.2 lbs (.09 kg)

Two Piece Center Cap Remover Set

Equipo de dos desmontadores de tapas centrales

Ensemble (2 pc) chapeau centrale de pneu

Set consists of: No. T65 (31565), No. T66 (31566).

Model	Item No.	Description	Weight
31564	31564	2 Pc. Center Cap Remover Set	.5 lbs (.22 kg)



Four-Way Lug Wrenches

Llaves cruz

Clés à goujon à quatre têtes

Ken-Tool offers the world's largest selection of quality lug wrenches, available in sizes to fit all your tire changing needs - SAE and Metric.

Professional Lug Wrenches

Llaves profesionales

Clés à goujon professionnelles



These wrenches are America's premier professional lug wrenches for cars, light trucks, SUV's, RV's, and vans. Drop-forged centers for extra strength. Keep wrenches in trunk for emergencies or everyday use.


Model	Item No.	Description	Socket Sizes	Length	Stock	Weight
T56	35656	Passenger	17, 19, 21, 22 mm	23" 58 cm	5/8" 16 mm	4 lbs 1.8 kg
T57®	35657	Passenger	3/4", 13/16", 7/8", 15/16"	23" 58 cm	5/8" 16 mm	4.5 lbs 2 kg

Standard Lug Wrenches

Llaves estándar

Clés à goujon standard

Welded center construction for strength and durability. Premium grade, special bar quality steel for extra strength.




Model	Item No.	Description	Socket Sizes	Length	Stock	Weight
T59	35659	Passenger	3/4", 13/16", 7/8", 15/16"	22" 56 cm	5/8" 16 mm	4.2 lbs 1.9 kg
T90	35690	Light Truck	7/8" deep well, 15/16", 1", 1-1/16"	25" 64 cm	3/4" 19 mm	7.2 lbs 3.2 kg

Economy Lug Wrenches

Llaves económicas

Clés à goujon économiques

These wrenches have fully welded centers which stand up to everyday use. 3/4" SAE is also 19 mm.



Model	Item No.	Description	Socket Sizes	Length	Stock	Weight
T9520	35620	Passenger	3/4", 13/16", 7/8", 17 mm	20" 51 cm	9/16" 14 mm	3.4 lbs 1.5 kg
T61	35661	Passenger	3/4", 13/16", 7/8", 17 mm	22" 56 cm	9/16" 14 mm	3.8 lbs 1.7 kg
T62	35662	Passenger	3/4", 13/16", 7/8", 17 mm	18" 46 cm	9/16" 14 mm	3.2 lbs 1.5 kg
T63	35663	Passenger	17, 19, 21, 22 mm	18" 46 cm	9/16" 14 mm	3.2 lbs 1.5 kg

Heavy-Duty Truck Lug Wrenches


Llaves para camiones de alta resistencia

Clés à goujon pour camions lourds

Use on heavy-duty trucks, buses, and tractors. Drop-forged or welded center provides strength and durability. **T95, TM95, T95A,** and **TC95** wrenches have center hole for a leverage bar. Socket sizes provided fit most metric or SAE lug nuts on today's trucks. Stock: 1" (25 mm).



Model	Item No.	Socket Sizes	Length	Weight
T95	35695	1-1/16", 1-1/4", 1-1/2", 13/16" square	27-1/2" 70 cm	13.8 lbs 6.2 kg
TM95 Metric	35795	24, 27, 30, 33 mm	27-1/2" 70 cm	13.5 lbs 6.1 kg



Model	Item No.	Socket Sizes	Length	Weight
TC95	35595	1-1/2", 13/16" square, 30, 33 mm	27-1/2" 70 cm	14.2 lbs 6.4 kg
T95A	35697	1-1/4", 1-1/2", 13/16" sq., 3/4" service arm	27-1/2" 70 cm	13.5 lbs 6.1 kg



Model	Item No.	Socket Sizes	Length	Weight
T96	35696	1-1/16", 1-1/4", 1-1/2", 13/16" square	27-1/2" 70 cm	13.5 lbs 6.1 kg

Economy Four-Way Lug Wrenches for the Do-It-Yourselfer

Llaves cruz económicas para aficionados

Clés à goujon à quatre têtes économiques pour le bricoleur

A complete line of lug wrenches value priced and merchandised to maximize your DIY business... And they're all tough and dependable

Passenger Car

Vehículo de pasajeros
Automobile




Chrome-plated finish, welded center. **Imported.**

Model	Item No.	Socket Sizes	Length	Stock	Weight
35630	35630	17 mm (11/16"), 19 mm (3/4"), 21 mm (13/16"), 22 mm (7/8")	20" 51 cm	5/8" 16 mm	3.7 lbs 1.7 kg
35635	35635	17 mm (11/16"), 19 mm (3/4"), 21 mm (13/16"), 22 mm (7/8")	14" 36 cm	5/8" 16 mm	2.6 lbs 1.2 kg

Folding Passenger Car

*Vehículo de pasajeros con
asientos plegables*
Voiture automobile, pliable




Chrome-plated finish. **Imported.**

Model	Item No.	Socket Sizes	Length	Stock	Weight
35633	35633	17 mm (11/16"), 19 mm (3/4"), 21 mm (13/16"), 22 mm (7/8")	14" 36 cm	9/16" 14 mm	2.7 lbs 1.2 kg

Telescoping Passenger Car

*Automóvil de pasajeros
con asientos extensibles*
*Voiture automobile,
téléscopique*




Chrome-plated finish. **Imported.**

Model	Item No.	Socket Sizes	Length	Stock	Weight
35634	35634	17 mm (11/16"), 19 mm (3/4"), 21 mm (13/16"), 23 mm (7/8")	21"(Extended) 53 cm		3 lbs 1.4 kg

Passenger Car

*Vehículo de
pasajeros*
Automobile




Painted finish, welded center.

Model	Item No.	Socket Sizes	Length	Stock	Weight
35637	35637	17 mm (11/16"), 19 mm (3/4"), 21 mm (13/16"), 22 mm (7/8")	18" 46 cm	9/16" 14 mm	3.6 lbs 1.6 kg

Light Truck/RV

*Camión liviano/
vehículo de
recreación*
Camionnette/VR



Painted finish, welded center.

Model	Item No.	Socket Sizes	Length	Stock	Weight
35638	35638	22 mm (7/8"), 24 mm (15/16"), 25 mm (1"), 27 mm (1-1/16")	23" 58 cm	11/16" 17.5 mm	5.6 lbs 2.5 kg

Power Wrench

Llave eléctrica

Clé à chocs



TR44SW Set



Designed for dual nut systems. Has 13/16" sq. end to hold inner nut, with a 1-1/2" hex drive to spin outer nut off. Also adaptable to remove any nut size with a **TR55** adapter. 3-to-1 ratio provides mechanical power advantage necessary to remove any stubborn nut found on trucks, farm vehicles, buses, aircraft, and RV's. Tremendous power allows one man operation. Heat-treated portable components for extra strength. All sockets are 3/4" drive.



Set No. TR43 (34543) Basic Power Wrench Set

Juego de llaves eléctricas básicas

Jeu de clés à chocs de base

Weight: 19 lbs. (8.6 kg)

Set contains:

Power Drive

TR45 (34543-02) 20-1/2" (52 cm) Bar Handle.

TR46 (34543-03) 20" (51 cm) Tube Handle.

Set No. TR44X (34545) Budd-Wheel Power Wrench Set

Juego de llaves eléctricas para ruedas tipo Budd

Jeu de clés à chocs pour roues à disque

The 3/4" service adapter allows you to use any 3/4" drive socket. Drive end is 1-1/2" hex. 13/16" square adapter for inner nut.

Weight: 20 lbs. (9.1 kg)

Set contains:

Power Drive

TR45 (34543-02) 20-1/2" (52 cm) Bar Handle.

TR52 (34543-15) 13/16" Sq. Adapter

TR53 (34543-16) 36" (91 cm) Tube Handle.

TR55 (34543-17) 3/4" Service Adapter

Set No. TR44SW (34547) Universal Power Wrench Set

Juego de llaves eléctricas universales

Jeu de clés à chocs universelles

Weight: 29 lbs. (13.2 kg)

Set contains:

Power Drive

TR45 (34543-02) 20-1/2" (52 cm) Bar Handle.

TR53 (34543-16) 36" (91 cm) Tube Handle.

TR52 (34543-15) 13/16" Square Adapter

TR55 (34543-17) 3/4" Service Adapter

Impact sockets:

S20 (30128) 7/8" **S24 (30136)** 1-1/8"

S21 (30130) 15/16" **S25 (30138)** 1-3/16"

S23 (30134) 1-1/16" **S33 (30133)** 33 mm

Double-End Truck Wrenches

Llaves dobles para camiones

Clés à double tête pour camions



Use on trucks, buses, farm, and off-road vehicles. Great for on-the-road service. Sizes available for all SAE and metric lug nuts. All wrenches are forged from 1" alloy steel for long lasting strength. Length: 16" (41 cm). Use TR5 truck wrench handle.

SAE • SOCIEDAD DE INGENIEROS AUTOMOTRICES (SAE)

Model	Item No.	Sockets Sizes	Weight
TR1	32501	1-1/8" with 13/16" Sq. x 1-1/2"	4.6 lbs (2 kg)
TR2	32502	1" with 5/8" Sq. x 1-1/4"	4.3 lbs (1.9 kg)
TR3	32503	7/8" x 1-1/16"	4.5 lbs (2 kg)
TR3A	32505	1-1/16" x 1-1/8"	4.5 lbs (2 kg)
● TR3X	32506	1-3/16" x 1-3/16" 1-3/4" Stud Depth	4.6 lbs (2 kg)
TR98	32508	1-1/2" x 13/16" Sq.	4.5 lbs (2 kg)
TR9	32509	1-1/4" x 1-1/16"	4.4 lbs (2 kg)

Caterpillar and Bobcat equipment, and hub piloted wheels.

NEW TR2A	32512	1" with 5/8" sq x 1-3/16"	4.5 lbs (2.0 kg)
-----------------	-------	---------------------------	------------------

METRIC • MÉTRICO • MÉTRIQUE

Model	Item No.	Sockets Sizes	Weight
⊗ TRM1	32551	17 mm sq. x 35 mm	4.5 lbs (2 kg)
TRM2	32552	24 mm x 33 mm	4.4 lbs (2 kg)
● TRM3	32553	27 mm x 30 mm 1-3/4" Stud Depth	4.6 lbs (2 kg)
TRM6	32556	21 mm sq. x 41 mm	4.5 lbs (2 kg)
● TRM7	32557	30 mm x 33 mm 1-3/4" Stud Depth	4.6 lbs (2 kg)

Metric inner and outer Budd nuts, and hub piloted wheels.

NEW TRM6A	32559	33 mm with 21 mm sq x 41 mm	4.5 lbs (2 kg)
------------------	-------	-----------------------------	----------------

⊗ **OBSOLETE** ● Updated with longer stud clearance – 1-3/4" stud depth

SAE / METRIC

SAE inner and outer Budd nuts, and hub piloted wheels.

Model	Item No.	Sockets Sizes	Weight
NEW TR99	32519	33 mm with 13/16" sq x 1-1/2"	4.5 lbs (2 kg)

Heavy-Duty Truck Wrench

Llaves para camiones de alta resistencia

Clé robuste pour camions



Use for off-the-road Budd-type wheels. Use TR11 handle. Long length provides extra leverage. Stock: 1-1/4" (3.1 cm)

Model	Item No.	Length	Socket Size	Weight
TR10	34401	29-1/2" (75 cm)	1-3/4" Hex & 15/16" sq.	12.2 lbs (5.5 kg)

Truck Wrench Handle

Mango de llave para camiones

Manche de clé pour camions



Heat-treated for strength and durability. Fits all Ken-Tool Double-end truck wrenches




Model	Item No.	Length	Stock	Weight
TR5	32318	22" (56 cm)	3/4" Hex	2.7 lbs (1.2 kg)
TR11	34402	30" (76 cm)	1" Round	6.5 lbs (2.9 kg)
NEW TR5A	32319	30" (76 cm)	3/4" Hex	7 lbs (3.2 kg)

Extra Leverage 1-1/2" Lug Nut Wrench

Llave de tuercas de rueda de 1-1/2" con mayor palanca

Clé pour écrou de roue de 1,5 po à effet de levier supplémentaire



Break loose stubborn nuts.
CAUTION: Not for tightening!
Original Military Version.
Provides up to 700 ft-lbs of torque!

Model	EDP No	Length	Socket Size	Weight
NEW 34420	34420	25.5" (64.7 cm)	1.5" Hex (3.8 cm)	14 lbs (6.4 kg)
		44" Extended (111.7 cm)	1.24" Depth (3.1 cm)	

Wrench Support Stand

Base de soporte para llave

Support de soutien pour clé



Commercial-duty stand used to support a double-end truck wrench, a 4-way lug wrench, or a torque wrench, when removing or replacing lug nuts. Adjusts from 14-1/2" to 22-1/2" high.





Wrench Support Stand

Model	Item No.	Weight
32610	32610	5.5 lbs (2.5 kg)

No-Mar Rim Guard™

Tapa para llantas No-Mar

Protection de jante antimarque



Protective cover prevents damage to chrome and aluminum rims and wheels when removing or replacing lug nuts. Imprinted with torque sequence number for proper torquing of disc wheels. **Imported from Canada.**

Model	Item No.	Description	Weight
30605	30605	Protective plastic cover	.5 lbs (.2 kg)

Ken-Tool®
WHEREVER TIRES ARE CHANGED™

TIRE & WHEEL SERVICE CENTER

Featuring 21 of Ken-Tool's most popular tire tool products!



Eye-catching 15" x 17" full color display card with photos and descriptions!

Convenient mobile base makes positioning for optimum sales a breeze!

Besides featuring 21 of Ken-Tool's most popular tire tool products, this new merchandiser attracts attention! It features a large 15" x 17" color display card at eye level with high-res color photos and descriptions of some of our best selling products. Each photo has a box so that a 1" x 2.5" barcode price label can be added.

The sturdy 12" x 16" freestanding, powder-coated wire rack features bright color graphics to let your customers know they are buying Ken-Tool's professional quality tire tools and lug wrenches. Included at no extra cost is a 3" high 4-wheel dolly with strong and durable caster wheels to enable the loaded rack to be easily moved to different locations and to facilitate floor cleaning. The rack and dolly take up a small 15" x 16" footprint and can be placed on the floor or, without the dolly, on a standard 18" gondola base shelf.

Tire & Wheel Service Center No. 36047

Centro de mantenimiento para ruedas y llantas No. 36047

Centre de service pneus et roues no 36047

Set No. 36047 Weight: 125 Lbs (57 kg) Shipped in 5 boxes.

Set Includes:

Model	Description	Quantity
35110	18" 35110 USA Hickory Tire Knocker	2
32119	24" T19 Straight Tire Spoon	2
33220	30" T20A Curved Tire Spoon	2
34645	37" T45A® Tubeless Tire Iron	2
34645C	37" T45AC® Classic Tubeless Tire Iron	2
34647	41" T45HD HD Tubeless Tire Iron	2
34747	36" T46A Tubeless Tire Iron	2
35323	16-1/2" T35 HD Tire Hammer, Wood Handle	1
35429	32" TG11E Bead Breaking Wedge, Fiberglass Handle	1
35637	18" 35637 Passenger 4-Way Lug Wrench, SAE/Metric	2
35638	23" 35638 Light Truck/RV 4-Way Lug Wrench, SAE/Metric	2
35595	27" TC95 HD Truck Lug Wrench, Popular Lug Sizes	1
30720	Wire Rack	1
36047-10	Planogram Card with Tie Strap	1



Professional Tire Tool and Lug Wrench Merchandisers

Comerciantes de llaves y herramientas para llantas profesionales
Présentoirs de clés à goujon et de démonte-pneus professionnels



35648

Ken-Tool offers a simple, yet effective way to merchandise our top products. With assortment #36046 you get 15 of our best selling tools. Assortment #36045 offers a larger assortment of 20 equally fast-selling tire and wheel service tools. Both assortments come complete with a sturdy, freestanding wire rack (no assembly required). The graphics on the front of the rack let your customer know they're buying professional quality tire tools and lug wrenches from Ken-Tool while the userfriendly design of the rack lets you know you found the solution to displaying Ken-Tool products. Both the wire rack and planogram card can be purchased separately.

10 Piece Lug Wrench Assortment with rack No. 35648

10 piezas. Surtido de llaves para ruedas con soporte No. 35648
Jeu de clés à goujon avec râtelier de 10 pièces no 35648

Set No. 35648 Weight: 50 Lbs (23 kg). **Set Includes:**

Model	Description	Quantity
35620	T9520 4-Way Wrench	2
35636	T56 Deluxe Metric 4-Way Wrench	1
35657	T57 4-Way Lug Nut Wrench	2
35659	T59 4-Way Lug Nut Wrench	2
35663	T63 Metric 4-Way Wrench	1
35690	90 4-Way Wrench - Truck	2
35648-01	Empty Display Stand	1

Deluxe Tire & Wheel Service Center No. 36045

Centro de mantenimiento para ruedas y llantas de lujo No. 36045
Centre de service de luxe pneus et roues no 36045

Set No. 36045 Weight: 128 Lbs (58 kg). **Set Includes:**

Model	Description	Quantity
32318	22" TR5 Truck Wrench Handle/Leverage Bar	2
32501	16" TR1 1-1/8" Hex with 13/16" Sq. x 1-1/2" Hex Double-End Wrench	1
32508	16" TR98 1-1/2" Hex x 13/16" Sq. Double-End Wrench	1
32509	16" TR9 1-1/4" Hex x 1-1/16" Hex Double-End Wrench	1
32552	16" TRM2 24 mm x 33 mm Double-End Wrench"	1
33220	30" T20A Curved Tire Spoon	2
33223	30" T23A Truck Lock Ring Removal Tool	1
34645	37" T45A Truck Tire Mount/Demount Iron	2
34647	41" T45HD Truck Tire Mount/Demount Iron	1
35229	31" TG11EH Fiberglass Replacement Handle (fits 35429)	1
35323	16.5" T35 Hickory Handled Tire Hammer	1
35429	32" TG11E Fiberglass Handled Bead Breaking Wedge	1
35690	25" T90 Light Truck 4-Way, Welded - SAE	2
35595	27" TC95 Heavy-Duty Truck 4-Way, Drop-Forged - SAE	2
35924	46" T24B Slide-Action, Impact Bead Breaker	1
30720	Wire Rack	1
36045-10	Planogram Card with Tie Strap	1



36045

Tire & Wheel Service Center No. 36046

Centro de mantenimiento para ruedas y llantas No. 36046
Centre de service pneus et roues no 36046

Set No. 36046 Weight: 73 Lbs (33 kg). **Set Includes:**

Model	Description	Quantity
32116	16" Small Tire Mount/Demount Spoon	2
33220	30" T20A Curved Tire Spoon	1
33223	30" T23A Truck Lock Ring Removal Tool	1
34645	37" T45A Truck Tire Mount/Demount Iron	2
35129	30" T11EH Hickory Replacement Handle (fits 35329)	1
35229	31" TG11EH Fiberglass Replacement Handle (fits 35429)	1
35429	31" TG11E Fiberglass Handled Bead Breaking Wedge	1
35620	20" T9520 Economy Passenger Car 4-Way - SAE	1
35657	23" T57 Professional Gold Passenger Car 4-Way - SAE	1
35659	22" T59 Professional Passenger Car 4-Way - SAE	1
35663	18" T63 Economy Passenger Car 4-Way - Metric	1
35690	25" T90 Light Truck 4-Way, Welded - SAE	1
35695	27" T95 Heavy-Duty Truck 4-Way, Drop-Forged - SAE	1
30720	Wire Rack	1
36046-10	Planogram Card with Tie Strap	1




36046

Tire Inflation Cages • Cajas para inflado de llantas • Cages de sécurité pour gonflement de pneus



Mandatory for any shop working with tubeless and multi-piece rims. Made from heavy-gauge steel tubing welded to a steel base. Guards against blown lock rings and rims. Follow OSHA regulation 29-CFR Part 1910.177. Read safety label on cage. Designed to meet OSHA regulation requirements for Medium, Heavy-Duty Truck, OTR, Tractor, and Super Singles. Ken-Tool offers sizes and designs for all your needs. For additional safety labels or instructions, call Ken-Tool customer service.

** For reference only. Height A** refers to the approximate height to the inside bend of the cage. May accommodate taller tires.



Work safely.
Always use an inflation cage when inflating tires.
Follow OSHA regulation 29-CFR Part 1910.177 whenever changing tires.

Passenger and Light Truck Cage

Jaula para camión liviano y para pasajeros

Cabine passager et véhicule utilitaire léger

A must for run-flat, low-profile, and other tires that are difficult to seat.



Why Tire Cages are Important

Model	Item No.	Height A**	Width B	Base	Weight
T103	36003	30"	16"	21-1/2" x 22"	80 lbs
		76 cm	41 cm	55 cm x 56 cm	36.2 kg

Portable Wide Base Cage

Caja con base amplia portátil

Cage portative à base large

Especially designed for wide base tires, this portable inflation cage will hold super singles, and super wide radial tires.

Fits comparable tires up to: 455/55R 22.5 Wide Super Single.



Model	Item No.	Height A**	Width B	Base	Weight
T101A	36007	43-1/2"	20-1/2"	7" closed x 27"	72 lbs
		111 cm	52 cm	18 cm closed x 69 cm	32.6 kg

Portable 2-Bar Cage

Caja de dos barras portátil • Cage portative à deux barres

Model	Item No.	Height A**	Width B	Base	Weight
T101	36001	41"	16"	7" closed x 21-1/2"	60 lbs
		104 cm	41 cm	18 cm closed x 55 cm	27.2 kg



4-Bar Cage

Caja de 4 barras
Cage à 4 barres

5-Bar Cage

Caja de 5 barras
Cage à 5 barres

3-Bar Cage

Caja de 3 barras
Cage à 3 barres

Model	Item No.	Description	Height A**	Width B	Base	Weight
T102	36002	4-Bar Cage	43-1/2"	20-1/2"	31-1/2" x 26"	146 lbs
			111 cm	52 cm	80 cm x 66 cm	66.2 kg
T105	36005	5-Bar Cage	43-1/2"	20-1/2"	41" x 26"	182 lbs
			111 cm	52 cm	104 cm x 66 cm	82.5 kg
T106	36006	3-Bar Cage	43-1/2"	20-1/2"	26" x 22"	134 lbs
			111 cm	52 cm	66 cm x 56 cm	60.7 kg

3-Bar Cage (OTR)

Caja de 3 barras (de carretera)

Cage à 3 barres (pneus tout terrain)



Model	Item No.	Height A**	Width B	Base	Weight
T104	36004	65"	24"	30" x 27"	158 lbs
		165 cm	61 cm	76 cm x 69 cm	72.6 kg

7-Bar Cage

Caja de 7 barras

Cage à 7 barres



Model	Item No.	Height A**	Width B	Base	Weight
NEW T108	36008	46"	29"	34" x 56"	485 lbs
		117 cm	74 cm	86 cm x 142 cm	220 kg

Checkout Ken-Tool's
**NEW EARTHMOVER
TIRE INFLATION CAGE**
NUEVA JAULA DE INFLADO PARA
NEUMÁTICOS DE EXCAVADORAS
NOUVELLE CAGE DE GONFLAGE
DE PNEU D'ENGIN DE GÉNIE CIVIL

**"World's Largest
Single-Piece Inflation Cage"**

See page 6



WARNING: Tire changing can be dangerous, and should be done only by trained personnel using proper tools and equipment as directed by Federal OSHA Standard No. 29 CFR Part 1910.177. Tires may explode during inflation causing injury to operator or bystander. Wear safety goggles. Keep all parts of body outside cage. Use extension hose, clip-on chuck, and remote valve. See supervisor for safety procedures.


WARNING: Do not alter cage in any way. Cage must be freestanding and at least three feet from other objects. Discard cage if bent, cracked, or otherwise damaged. Always wear safety goggles.

Truck Tire Changing Stand

Soporte para cambio de llantas de camiones
Support de démontage pour pneus de camions

Stand handles wheels or open rims 16.5" to 24". Double-slide adjustment with locking device prevents twisting so it stays aligned with the wheel or rim. Stand is the ideal height for driving off beads or demounting tires. It must be used to be appreciated.

Model	Item No.	Weight
T115	36015	21 lbs (9.5 kg)



Easy-Lift™ Bead Seating Stand

Soporte para calzado de talón Easy-Lift™
Poste de portée de talon Easy-Lift™



SAFETY FIRST!

ERGONOMIC:
Easy operation with less back strain. Makes concentric bead seating safe and easy!



EasyLift™
Bead Seating
Stand



Push tubeless assembly onto crown – tire and wheel will automatically fall onto center of stand and rest with bead centered on bottom wheel flange




After seating bead step around stand and easily lift assembly into vertical position

ERGONOMIC: Reduces back strain while handling 24.5" tubeless tire & wheel assemblies. Aligns beads concentrically on wheel for improved ride & longer tire life. Portable for field service, or can be bolted to the floor. Made of high grade steel. Length: 24" high x 26" wide x 27" long. **PATENTED.**

Model	Description	Weight
36016	Standard Crown for 8-3/4" diameter hubs	36 lbs (16.4 kg)
36017	Large Crown for 11" Euro hubs	37 lbs (16.8 kg)

EZ Tire Rotator™

Rotador de neumáticos EZ Tire Rotator®
Rotateur de pneu EZ Tire Rotator®



Quickly rotate assembly inside cage for easy valve access — no more hassle!



Reduces handling, back strain and user fatigue; increases safety. Easily installed or moved to another cage – no fastening required. No assembly required, simply place in the center of the cage. Works as a portable tread inspection and stone removal station outside of cage. Features heavy-duty 2" ball-bearing steel rollers and 1-1/4" thick steel stock for long service. Boxed and UPS shippable. Patent pending.

EZ Tire Rotator™ fits any Ken-Tool® 3-Bar, 4-Bar and 5-Bar Inflation Cage, plus many competitive cages

Model	Item No.	Description	Length	Weight
NEW T114	36014	T114 EZ Tire Rotator	17-1/2" (44.5 cm) x 25-1/2" (64.8 cm) x 2-1/2" (6.4 cm)	19 lbs (8.6 kg)

Have a new idea? E-mail sales@kentool.com

For more information visit us at www.kentool.com



BEARING & ROTOR PULLING SYSTEM
SISTEMA DE TRACCIÓN DE ROTORES Y RODAMIENTOS
SYSTÈME D'EXTRACTION DE
ROTORS & DE COUSSINETS

Includes everything you need to do the job!







HubShark® Demo


Replace the front wheel bearings on front wheel drive vehicles without removing the steering knuckle from the vehicle – in about 20 minutes per wheel.

- *Keep more jobs in house - don't send bearings out to be machine pressed*
- *Save time and money with reduced down time*
- *Pull and press any hub or bearing on domestic and import vehicles*
- *Pull inner bearing race from the hub*
- *Done completely on vehicle - no need to remove the knuckle assembly and re-align the front end*
- *Always be sure the center screw thread is clean and well lubricated*
- *Always wear safety goggles*
- *See www.kentool.com for instruction manual*

Model	Description	Weight
7326	Pro Super Hub-Shark System®	58 lbs (26.3 kg)

No. 7326U Upgrade Kit available for previous Hub-Shark™ owners (case included)





All of Ken-Tool's Professional Vises feature:

- 360° swivel base
- Machined base plate for smooth swivel
- Heavy-duty jaw beam covers screw
- Built-in anvils



Jaw faces have "V" notches for vertical gripping




Built-in pipe jaws

"V" notched, replaceable/reversible jaws made of carbon steel and heat-treated for extra strength, diamond cut on one side - smooth on the other




- Gear-type locking system with double lock-down bolts - locks vise securely in position



Professional Reversible Mechanic's Vises feature:

It's simple...Remove the jaw from the front of the base, swivel the base 180°, then re-insert the jaw:



Standard Position

Reverse Position

2 Built-in anvils provide more work surface area than any other vise




Professional Workshop Vises

Tornillos de banco para taller profesionales

Étaux pour ateliers professionnels

With high quality construction for extra durability and full-strength performance at any jaw opening, these vises are made for the professional - strong, durable, and built to last.




K65 6-1/2"

Model	Item No.	Jaw Width	Jaw Opening	Throat Depth	Pipe Jaw Capacity	Weight
K55	64055	5-1/2" 14 cm	7-1/2" 19.1 cm	3-1/4" 8.3 cm	1/8" - 2-1/2" .3 - 6.4 cm	27 lbs 12.3 kg
K65	64065	6-1/2" 16.5 cm	9" 22.9 cm	3-7/8" 9.8 cm	1/8" - 3-1/2" .3 - 8.9 cm	38 lbs 17.3 kg

Professional Reversible Mechanic's Vises

Tornillos de banco reversibles para mecánicos profesionales

Étaux professionnels réversibles de mécanicien



2 Built-in anvils provide more work surface area than any other vise

KT4800 8"

With our Reversible Vises you get all of the high quality features and rugged durability of the Pro Workshop Vises, and more! Significantly increase your gripping capacity when you reverse the position of the front jaw.

Model	Item No.	Jaw Width	Jaw Opening	Throat Depth	Pipe Jaw Capacity	Weight
KT4650	64650	6-1/2" 16.5 cm	9" - 12" 22.9 - 30.5 cm	4" 10.1 cm	1/8" - 4" .3 - 10.1 cm	52 lbs 23.6 kg
KT4800	64800	8" 20.3 cm	11 - 14" 28 - 35.6 cm	4-7/8" 12.4 cm	1/8" - 4-1/4" .3 - 10.8 cm	74 lbs 33.6 kg

Professional C-Clamps

Abrazaderas en C profesionales

Serre-joints en C professionnels

This c-clamp is for the professional. Designed for strength and toughness, with sliding pin handle and acme-thread screw. Imported.



Model	Item No.	Jaw Opening	Depth	Screw Diameter	Std. Pack	Weight
KT-4	39604	4" 10 cm	2-1/16" 5 cm	5/8" 1.5 cm	6	1.8 lbs .8 kg
KT-6	39606	6" 15 cm	2-3/4" 7 cm	5/8" 1.5 cm	6	2.5 lbs 1.1 kg
KT-8	39608	8" 20 cm	3-1/4" 8 cm	3/4" 2 cm	1	3.5 lbs 1.6 kg



Torque Master® Torque Limiting Sockets

Llaves de tubo limitadoras del par motor principal • Douilles de limitation de couple Torque Master

For foreign and domestic cars and light trucks. Tighten nuts to factory specifications each time the wheels are replaced. Color and letter coded for quick size and torque reference. Converts any impact gun, including those with an extended anvil, into an instant torque wrench by bleeding torque off the impact gun. Application chart can be wall mounted. Application Charts No. 30199 and No. 30299 are also available separately. Limited lifetime warranty.



Four Piece Starter Kit

**Equipo básico de cuatro piezas
kit de base de quatre pièces**

Set contains:

- 30181** - Brown (A) 100 ft/lbs.
- 30183** - Gray (C) 100 ft/lbs.
- 30185** - Blue (E) 80 ft/lbs.
- 30189** - White (I) 120 ft/lbs.



Model	Item No.	Weight
30174	30174	4.4 lbs (2 kg)



Six Piece Kit

**Juego de seis piezas
Kit six pièces**

Set contains:

- 30181** - Brown (A) 100 ft/lbs.
- 30183** - Gray (C) 100 ft/lbs.
- 30184** - Black (D) 60 ft/lbs.
- 30185** - Blue (E) 80 ft/lbs.
- 30186** - Yellow (F) 65 ft/lbs.
- 30189** - White (I) 120 ft/lbs.



Model	Item No.	Weight
30176	30176	6.9 lbs (3.1 kg)



Nine Piece Kit

**Juego de nueve piezas
Kit neuf pièces**

Set contains:

- 30181** - Brown (A) 100 ft/lbs.
- 30182** - Orange (B) 80 ft/lbs.
- 30183** - Gray (C) 100 ft/lbs.
- 30184** - Black (D) 60 ft/lbs.
- 30185** - Blue (E) 80 ft/lbs.
- 30186** - Yellow (F) 65 ft/lbs.
- 30187** - Red (G) 80 ft/lbs.
- 30188** - Dark Green (H) 45 ft/lbs.
- 30189** - White (I) 120 ft/lbs.



Model	Item No.	Weight
30179	30179	8.75 lbs (4 kg)



Ten Piece Kit

**Juego de diez piezas
Kit dix pièces**

Set contains:

- 30181** - Brown (A) 100 ft/lbs.
- 30182** - Orange (B) 80 ft/lbs.
- 30183** - Gray (C) 100 ft/lbs.
- 30184** - Black (D) 60 ft/lbs.
- 30185** - Blue (E) 80 ft/lbs.
- 30186** - Yellow (F) 65 ft/lbs.
- 30187** - Red (G) 80 ft/lbs.
- 30188** - Dark Green (H) 45 ft/lbs.
- 30189** - White (I) 120 ft/lbs.
- 30200** - Aqua (Q) 140 ft/lbs.



Model	Item No.	Weight
30180	30180	9.5 lbs (4.3 kg)



Twelve Piece Kit

**Juego de doce piezas
Kit douze pièces**

Set contains:

- 30181** - Brown (A) 100 ft/lbs.
- 30182** - Orange (B) 80 ft/lbs.
- 30183** - Gray (C) 100 ft/lbs.
- 30184** - Black (D) 60 ft/lbs.
- 30185** - Blue (E) 80 ft/lbs.
- 30186** - Yellow (F) 65 ft/lbs.
- 30187** - Red (G) 80 ft/lbs.
- 30188** - Dark Green (H) 45 ft/lbs.
- 30189** - White (I) 120 ft/lbs.
- 30200** - Aqua (Q) 140 ft/lbs.
- 30202** - Navy Blue (Y) 100 ft/lbs.
- 30213** - Gold (NN) 90 ft/lbs.



Model	Item No.	Weight
30190	30190	10.5 lbs (4.8 kg)



Four Piece Torque Stick Set for SUV's

Most Popular Sizes for Largest Growing Market

**Juego de palancas de par motor de cuatro piezas
para los tamaños más populares de vehículos todo t
erreno para el mayor mercado en crecimiento**

**Kit de quatre bras de torsion convenant aux
VUS de dimensions les plus populaires idéal pour un
marché de plus en plus grand**

For domestic and foreign SUV's. Tighten lug nuts to factory specifications. Color and letter coded for quick size and torque reference.

Set contains:

- 30181** - Brown (A) 100 ft/lbs.
- 30183** - Gray (C) 100 ft/lbs.
- 30200** - Aqua (Q) 140 ft/lbs.
- 30204** - Turquoise (BB) 150 ft/lbs.

Model	Item No.	Weight
30175	30175	4.5 lbs (2 kg)



Torque Extension Kits

**Juegos de extensiones para
torque**

Kits de rallonges de couple

Convert your own sockets into torque sockets.

Four Piece Extension Kit for Passenger Car - 1/2" Drive

**Juego de extensión de cuatro piezas para automóviles
de pasajeros - entrada de 1/2 pulgada**

**Kit de rallonge de quatre pièces pour
automobiles - Prise 1/2 po**

Set contains:

- 30223** - Gray (C) 100 ft/lbs
- 30225** - Blue (E) 80 ft/lbs
- 30226** - Yellow (F) 65 ft/lbs
- 30229** - White (I) 120 ft/lbs

Model	Item No.	Weight
30234	30234	3 lbs (1.3 kg)



Five Piece Extension Kit for Passenger Car - 1/2" Drive

Juego de extensiones de cinco piezas para automóviles.

Cuadro de 1/2"

Kit (cinq pièces) de rallonges pour voitures - prise demi pouce

Set contains:

30220	- Aqua (Q)	140 ft/lbs.
30223	- Gray (C)	100 ft/lbs.
30225	- Blue (E)	80 ft/lbs.
30226	- Yellow (F)	65 ft/lbs.
30229	- White (I)	120 ft/lbs.

Model	Item No.	Weight
30235	30235	4 lbs (1.8 kg)



Ten Piece Extension Kit for Passenger Car & Light Truck

Juego de extensiones de diez piezas para automóviles y camiones livianos

Kit (dix pièces) de rallonges pour voitures et camions légers

Set contains:

30220	- Aqua (Q)	140 ft/lbs.
30223	- Gray (C)	100 ft/lbs.
30224	- Black (D)	60 ft/lbs.
30225	- Blue (E)	80 ft/lbs.
30226	- Yellow (F)	65 ft/lbs.
30228	- Dark Green (H)	45 ft/lbs.
30229	- White (I)	120 ft/lbs.
30248	- Light Purple (K)	110 ft/lbs.
30249	- Neon Yellow (OO)	75 ft/lbs.
30274	- Gold (NN)	90 ft/lbs.

Model	Item No.	Weight
30251	30251	7.6 lbs (3.5 kg)



Individual Sockets & Extensions

Dados y extensiones individuales

Douilles individuelles et rallonges



Individual Sockets

Dados individuales

Douilles individuelles



WC 30199

Model	Description	Socket Opening	Torque Limit	Weight
30181	Brown (A)	13/16"	100 ft-lbs	.5 lbs (.2 kg)
30182	Orange (B)	21 mm	80 ft-lbs	.5 lbs (.2 kg)
30183	Gray (C)	19 mm (3/4")	100 ft-lbs	.5 lbs (.2 kg)
30184	Black (D)	21 mm	60 ft-lbs	.5 lbs (.2 kg)
30185	Blue (E)	19 mm (3/4")	80 ft-lbs	.5 lbs (.2 kg)
30186	Yellow (F)	19 mm (3/4")	65 ft-lbs	.5 lbs (.2 kg)
30187	Red (G)	17 mm	80 ft-lbs	.5 lbs (.2 kg)
30188	Dark Green (H)	17 mm	45 ft-lbs	.5 lbs (.2 kg)
30189	White (I)	7/8"	120 ft-lbs	.5 lbs (.2 kg)
30195	Tan (J)	1"	140 ft-lbs	.5 lbs (.2 kg)
30196	Light Purple (K)	17 mm	110 ft-lbs	.5 lbs (.2 kg)
30197	Green (L)	1"	170 ft-lbs	.5 lbs (.2 kg)
30198	Crimson Red (V)	1-1/16"	140 ft-lbs	.5 lbs (.2 kg)
30200	Aqua (Q)	7/8"	140 ft-lbs	.5 lbs (.2 kg)
30201	Bright Green (T)	15/16"	135 ft-lbs	.5 lbs (.2 kg)
30202	Navy Blue (Y)	7/8"	100 ft-lbs	.5 lbs (.2 kg)
30203	Light Tan (Z)	7/8"	65 ft-lbs	.5 lbs (.2 kg)
30204	Turquoise (BB)	21 mm	150 ft-lbs	.5 lbs (.2 kg)
30205	Light Pink (CC)	17 mm	90 ft-lbs	.5 lbs (.2 kg)
30206	Sky Blue (DD)	21 mm	100 ft-lbs	.5 lbs (.2 kg)
30207	Safety Purple (EE)	22 mm	140 ft-lbs	.5 lbs (.2 kg)
30208	Yellow Gray (FF)	19 mm	180 ft-lbs	.5 lbs (.2 kg)
30211	Quartz Gray (KK)	19 mm	120 ft-lbs	.5 lbs (.2 kg)
30212	Fuchsia (LL)	22 mm	175 ft-lbs	.5 lbs (.2 kg)
30213	Gold (NN)	19 mm	90 ft-lbs	.5 lbs (.2 kg)
30214	Salmon (QQ)	22 mm	95 ft-lbs	.5 lbs (.2 kg)
30216	Deep Purple (UU)	14 mm	75 ft-lbs	.5 lbs (.2 kg)
30217	Vanilla (XX)	13/16"	160 ft-lbs	.5 lbs (.2 kg)
30218	Honey Yellow (JJ)	19 mm	145 ft-lbs	.5 lbs (.2 kg)
30222	Silver Sparkle (SS)	21 mm	110 ft-lbs	.5 lbs (.2 kg)
30199	11" x 17" Application Wall Chart (WC)		.5 lbs (.2 kg)	
30299	22" x 24" Laminated Socket Torque Wall Chart		.5 lbs (.2 kg)	



Individual Torque Extensions

Extensiones de torsión individuales

Rallonges de couple individuelles



Model	Description	Drive Size Socket/Opening	Torque Limit	Weight
30255	Black Oxide (A)	3/8"	30 ft-lbs	.5 lbs (.2 kg)
30256	Black Oxide (B)	3/8"	40 ft-lbs	.5 lbs (.2 kg)
30257	Black Oxide (C)	3/8"	50 ft-lbs	.5 lbs (.2 kg)
30258	Black Oxide (D)	3/8"	60 ft-lbs	.5 lbs (.2 kg)
30219	Orange (B)	1/2"	160 ft-lbs	.7 lbs (.3 kg)
30220	Aqua (Q)	1/2"	140 ft-lbs	.7 lbs (.3 kg)
30221	Light Blue (S)	1/2"	55 ft-lbs	.7 lbs (.3 kg)
30223	Gray (C)	1/2"	100 ft-lbs	.7 lbs (.3 kg)
30224	Black (D)	1/2"	60 ft-lbs	.7 lbs (.3 kg)
30225	Blue (E)	1/2"	80 ft-lbs	.7 lbs (.3 kg)
30226	Yellow (F)	1/2"	65 ft-lbs	.7 lbs (.3 kg)
30227	Fuchsia (LL)	1/2"	175 ft-lbs	.7 lbs (.3 kg)
30228	Dark Green (H)	1/2"	45 ft-lbs	.7 lbs (.3 kg)
30229	White (I)	1/2"	120 ft-lbs	.7 lbs (.3 kg)
30243	Turquoise (G)	1/2"	150 ft-lbs	.7 lbs (.3 kg)
30244	Bright Green (T)	1/2"	135 ft-lbs	.7 lbs (.3 kg)
30247	Gold (NN)	1/2"	90 ft-lbs	.7 lbs (.3 kg)
30248	Light Purple (K)	1/2"	110 ft-lbs	.7 lbs (.3 kg)
30249	Neon Yellow (OO)	1/2"	75 ft-lbs	.7 lbs (.3 kg)
30250	Green (L)	1/2"	170 ft-lbs	.7 lbs (.3 kg)

Individual Heavy-Duty Truck Torque Extensions

Extensiones de torsión individuales de alta resistencia para camiones

Rallonges individuelles robustes de couple pour camions



Convert your own sockets into torque sockets for use on commercial, heavy-duty trucks, and buses.

Model	Description	Drive Size Socket/Opening	Torque Limit	Weight
30230	Yellow (O)	3/4"	175 ft-lbs	.75 lbs (.3 kg)
30231	Yellow (N)	3/4"	250 ft-lbs	.75 lbs (.3 kg)
30232	Yellow (U)	3/4"	350 ft-lbs	.75 lbs (.3 kg)
30233	Yellow (M)	3/4"	475 ft-lbs	.75 lbs (.3 kg)
30236	Yellow (T)	1"	175 ft-lbs	1 lb (.5 kg)
30237	Yellow (R)	1"	250 ft-lbs	1 lb (.5 kg)
30238	Yellow (S)	1"	350 ft-lbs	1 lb (.5 kg)
30239	Yellow (P)	1"	475 ft-lbs	1 lb (.5 kg)
30240	Yellow (W)	1"	650 ft-lbs	1 lb (.5 kg)
30241	Yellow (Q)	1"	300 ft-lbs	1 lb (.5 kg)
30242	Yellow (Y)	1"	550 ft-lbs	1 lb (.5 kg)

WARNING: Torque sockets and truck torque extensions cannot be used to take off wheel nuts. Calibrate your impact gun and follow all manufacturers' recommended procedures when using Torque Master products.

For more information visit us at www.kentool.com

Wheel Cover & Wheel-Lock Removal Kits

Juego de extracción de cubiertas y anillos de retención de ruedas

Kit d'outils de démontage des enjoliveur et bloqueur de roue

Nine Piece Kit

Juego de nueve piezas

Kit neuf pièces

Remove and replace GM, Ford, Chrysler hubcap locks and aftermarket wheel lug locks without the factory issued key.

Save time! Will not damage the lock or stud.

Set contains:

- 30170-10** Ford & Chrysler Hubcap Locks/Lg. GM Triangle Wheel locks
- 30170-20** GM Spline Hubcap Locks
- 30170-30** GM Hubcap Locks
- 30170-40** 18 mm Lugs/GM Wheel Cover Locks/Ford Wheel Locks
- 30170-50** Corvette/GM "N" & "F" Body Wheel Locks
- 30170-60** Std. McGard-Style Wheel Locks/Lg. GM Wheel Cover
- 30170-70** Oversized McGard-Style Wheel Locks
- 30170-80** Punch
- 30170-90** Lg. Dia. Chrysler Lock



Model	Item No.	Drive	Weight
30170	30170	1/2"	3.1 lbs (1.4 kg)

Thirteen Piece Kit

Juego de trece piezas

Kit treize pièces

Set contains:

- 30170-10** Ford & Chrysler Hubcap Locks/Lg. GM Triangle Wheel Locks
- 30170-20** GM Spline Hubcap Locks
- 30115-02** 3/4", 19mm Damaged Wheel Lug & Oversized Wheel Lock Remover
- 30170-30** GM Hubcap Locks
- 30115-05** 7/8" Damaged Wheel Lug & Oversized Wheel Lock Remover
- 30170-40** 18 mm Lugs/GM Wheel Cover Locks/Ford Wheel Locks
- 30171-45** 18 mm Nut/Corvette GM Lock
- 30170-50** Corvette/GM "N" & "F" Body Wheel Locks
- 30170-60** Std. McGard-Style Wheel Locks/ Lg. GM Wheel Cover
- 30170-70** Oversized McGard-Style Wheel Locks
- 30170-80** Punch
- 30170-90** Lg. Dia. Chrysler Lock
- 30110-06** 3" Impact Extension



Model	Item No.	Drive	Weight
30171	30171	1/2"	4.9 lbs (2.2 kg)

Twist Sockets & Twist Socket Sets

Dados giratorios y juegos de dados giratorios

Douilles de torsion & jeux de douilles de torsion

Twist sockets are specifically designed to easily remove damaged, rounded or corroded nuts, wheel lugs, bolts, pipes, pipe nipples or studs. Simply place the socket so it barely catches the head of the fastener and turn with an air ratchet, hand ratchet, or breaker bar. The unique spiral fluting bites onto the damaged fastener and won't let go. Designed for general automotive applications.

Five Piece Deep Twist Socket Set

Juego de dados giratorios profundos de cinco piezas

Jeu de cinq douilles profondes de torsion

Socket sizes:

- 30116-02** 19 mm, 3/4" socket
- 30116-04** 13/16" socket
- 30116-05** 7/8" socket
- 30116-07** 15/16" socket
- 30116-08** 1" socket



Model	Item No.	Description	Drive	Weight
30116	30116	5 Pc. Set w/Organizer Bar	1/2"	2.5 lbs (1.1 kg)

Eight Piece Twist Socket Set

Juego de dados giratorios de ocho piezas

Jeu de huit douilles de torsion

Socket sizes:

- 30117-06** 6 mm socket
- 30117-08** 8 mm socket
- 30117-10** 10 mm socket
- 30117-12** 12 mm socket
- 30117-13** 13 mm socket
- 30117-14** 14 mm socket
- 30117-15** 15 mm socket
- 30117-17** 17 mm socket



Model	Item No.	Description	Drive	Weight
30117	30117	8 Pc. Set w/Organizer Bar	1/4"	.9 lbs (.4 kg)

Nine Piece Twist Socket Set

Juego de dados giratorios de nueve piezas

Jeu de neuf douilles de torsion

Socket sizes:

- 30106-05** 10 mm socket
- 30106-07** 7/16", 11 mm socket
- 30106-11** 12 mm socket
- 30106-13** 13 mm socket
- 30106-15** 14 mm socket
- 30106-19** 15 mm socket
- 30106-21** 5/8", 16 mm socket
- 30106-25** 17 mm socket
- 30106-27** 3/4", 19 mm socket



Model	Item No.	Description	Drive	Weight
30109	30109	9 Pc. Set w/Organizer Bar	3/8"	2.8 lbs (1.2 kg)

Thirteen Piece Twist Socket Set

Juego de dados giratorios de trece piezas

Jeu de treize douilles de torsion

Socket sizes:

- 30106-01** 3/8" socket
- 30106-05** 10 mm socket
- 30106-07** 7/16", 11 mm socket
- 30106-09** 1/2" socket
- 30106-11** 12 mm socket
- 30106-13** 13 mm socket
- 30106-15** 14 mm socket
- 30106-17** 9/16" socket
- 30106-19** 15 mm socket
- 30106-21** 5/8", 16 mm socket
- 30106-23** 11/16" socket
- 30106-25** 17 mm socket
- 30106-27** 3/4", 19 mm socket



Model	Item No.	Description	Drive	Weight
30108	30108	13 Pc. Set w/Organizer Bar	3/8"	1.6 lbs (.7 kg)

Five Piece Twist Socket Set with Punch

Juego de dados giratorios de cinco piezas con punzón

Jeu de cinq douilles de torsion avec poinçon

Socket sizes:

- 30118-03** 19 mm, 3/4" socket
- 30118-04** 13/16" socket
- 30118-05** 7/8" socket
- 30118-06** 15/16" socket
- 30118-07** 1" socket
- 30170-80** Punch



Model	Item No.	Description	Drive	Weight
30118	30118	5 Pc. Set w/Plastic Case	1/2"	2 lbs (.9 kg)

Nine Piece Twist Socket Set with Punch
Juego de dados giratorios de nueve piezas con punzón
Jeu de neuf douilles de torsion avec poinçon



Socket sizes:

- 30106-05 10 mm socket
- 30106-07 7/16", 11mm socket
- 30106-11 12 mm socket
- 30106-13 13 mm socket
- 30106-15 14 mm socket
- 30106-19 15 mm socket
- 30106-21 5/8", 16 mm socket
- 30106-25 17 mm socket
- 30106-27 3/4", 19 mm socket
- 30170-80 Punch



Model	Item No.	Description	Drive	Weight
30107	30107	9 Pc. Set w/Plastic Case	3/8"	1.5 lbs (.7 kg)

Thirteen Piece Twist Socket Set with Punch
Juego de dados giratorios de trece piezas con punzón
Jeu de treize douilles de torsion avec poinçon



Socket sizes:

- 30106-01 3/8" socket
- 30106-05 10 mm socket
- 30106-07 7/16", 11 mm socket
- 30106-09 1/2" socket
- 30106-11 12 mm socket
- 30106-13 13 mm socket
- 30106-15 14 mm socket
- 30106-17 9/16" socket
- 30106-19 15 mm socket
- 30106-21 5/8", 16 mm socket
- 30106-23 11/16" socket
- 30106-25 17 mm socket
- 30106-27 3/4", 19 mm socket
- 30170-80 Punch




Model	Item No.	Description	Drive	Weight
30106	30106	13 Pc. Set w/Plastic Case	3/8"	1.9 lbs (.9 kg)

Ten Piece Slim Twist Socket Set with External Hex
Juego de dados giratorios delgados con cuadro hexagonal externo
Jeu de dix douilles minces de torsion avec extérieur hexagonal

Quickly removes damaged or rounded nuts, bolts, studs, and socket head cap screws in tight quarters. The through hole design allows them to also be used on long studs. Fits SAE sizes 3/8" to 3/4" and metric sizes from 9mm up to 19mm. Used where standard twist sockets will not fit. Can be used with an open-end wrench, or with a socket.

Socket sizes:

- 30270-01 9 mm ; ext. hex 5/8" socket
- 30270-02 10 mm, 3/8" ; ext. hex 5/8" socket
- 30270-03 11 mm, 7/16" ; ext. hex 11/16" socket
- 30270-04 12 mm ; ext. hex 3/4" socket
- 30270-05 13 mm, 1/2" ; ext. hex 3/4" socket
- 30270-06 14 mm, 9/16" ; ext. hex 13/16" socket
- 30270-07 15 mm ; ext. hex 7/8" socket
- 30270-08 16 mm, 5/8" ; ext. hex 15/16" socket
- 30270-09 17 mm, 11/16" ; ext. hex 1" socket
- 30270-10 19 mm, 3/4" ; ext. hex 1-1/16" socket



Model	Item No.	Description	Drive	Weight
30270	30270	10 Pc. Set w/Organizer Bar	3/8"	1 lb (.5 kg)
30271	30271	10 Pc. Set w/Plastic Case	3/8"	1 lb (.5 kg)

● DISCONTINUED

Individual Twist Sockets - Fluted
Dados giratorios individuales, estriados
Douilles de torsion individuelles - cannelées



Model	Item No.	Socket Sizes	Fluted	Drive	Weight
30151	30151	3/4", 19 mm & 13/16", 21 mm	12	1/2"	.4 lbs (.18 kg)
30152*	30152	3/4", 19 mm & 13/16", 21 mm	6	1/2"	.4 lbs (.18 kg)
30153	30153	7/8" x 1"	12	1/2"	.4 lbs (.18 kg)
30154*	30154	7/8" x 1"	6	1/2"	.4 lbs (.18 kg)

*Includes punch pin

Flip Sockets & Impact Socket Sets
Dados abatibles y juegos de dados impacto
Douilles inversées & jeux de douilles à choc

Three Piece 6-Fluted Twist Flip Socket Set
Juego de dados abatibles giratorios con 6 estrías, tres piezas
Jeu de trois douilles de torsion inversées à 6 cannelures



Socket sizes:

- 30152 19 mm & 13/16", 21 mm socket, 6-Fluted
- 30154 7/8" & 1" socket
- 30110-06 3" extension



Model	Item No.	Description	Drive	Weight
30101	30101	3 Pc. Set w/Plastic Case	1/2"	1.3 lbs (.6 kg)

Three Piece 12-Fluted Twist Flip Socket Set
Juego de dados abatibles giratorios con 12 estrías, tres piezas
Jeu de trois douilles de torsion inversées à 12 cannelures



Socket sizes:

- 30151 19 mm & 13/16", 21 mm socket
- 30153 7/8" & 1" socket
- 30110-06 3" extension



Model	Item No.	Description	Drive	Weight
30102	30102	3 Pc. Set w/Plastic Case	1/2"	1.3 lbs (.6 kg)

Three Piece 6-Pt. & 12-Fluted Twist Flip Socket Set
Juego de dados abatibles giratorios, 6 puntas y 12 estrías, tres piezas
Jeu de trois douilles de torsion inversées à 12 cannelures et 3 points



Socket sizes:

- 30103-01 17 mm socket
- 30103-02 19 mm socket
- 30110-06 3" extension



Model	Item No.	Description	Drive	Weight
30103	30103	3 Pc. Set w/Plastic Case	1/2"	1.3 lbs (.6 kg)

SOCKETS AND SOCKET SETS HAVE A LIMITED LIFETIME WARRANTY

Six Piece Thick and Thin Flip Socket Set*
Juego de dados abatibles gruesos y delgados, seis piezas

Jeu de six douilles inversées fines et épaisse

For those ever changing aftermarket and manufacturers' wheels. One end is a standard 6-point socket for everyday use. Flip socket over and you have a thinwall socket of the same size for wheels with minimal clearance.

Socket sizes:

- 30112-01 17 mm socket
- 30112-02 19 mm, 3/4" socket
- 30112-03 21 mm socket
- 30112-04 13/16" socket
- 30112-05 7/8" socket
- 30110-06 3" extension

Model	Item No.	Drive	Weight
30112	30112	1/2"	3 lbs (1.3 kg)



Three Piece Thinwall Flip Socket Set

Juego de dados abatibles de pared delgada, tres piezas

Jeu de trois douilles inversées à paroi mince

One end is a standard 6-point socket for everyday use. Flip socket over and you have a 6-point socket of larger size.

Socket sizes:

- 30110-01 19 mm - 21 mm socket
- 30110-02 3/4" - 13/16" socket
- 30110-06 3" extension

Model	Item No.	Drive	Weight
30110	30110	1/2"	1.2 lbs (.54 kg)



Six Piece Deep Thinwall Impact Socket Set*
Juego de dados de impacto profundo de pared delgada, seis piezas

Jeu de six douilles profondes à choc à paroi mince

For the difficult aftermarket and manufacturers' wheels.

Socket sizes:

- 30113-01 17 mm socket
- 30113-02 19 mm, 3/4" socket
- 30113-03 21 mm socket
- 30113-04 13/16" socket
- 30113-05 7/8" socket
- 30110-06 3" extension

Model	Item No.	Drive	Weight
30113	30113	1/2"	3 lbs (1.3 kg)



Five Piece Thinwall Flip Socket Set*

Juego de dados abatibles de pared delgada, cinco piezas

Jeu de cinq douilles inversées à paroi mince

One end is a standard 6-point socket for everyday use. Flip socket over and you have a 6-point socket of larger size.

Socket sizes:

- 30110-01 19 mm - 21 mm socket
- 30110-02 3/4" - 13/16" socket
- 30119-03 7/8" - 15/16" socket
- 30119-04 17 mm - 19 mm socket
- 30110-06 3" extension

Model	Item No.	Drive	Weight
30119	30119	1/2"	2.1 lbs (1 kg)



Five Piece Double-Duty

Oil Drain Plug Removal Flip Socket Set

Juego de dados abatibles para extracción del tapón del cárter de aceite de doble servicio, cinco piezas

Jeu de cinq douilles inversées à double fonction d'extraction de bouchon de purge d'huile

One end is a standard 6-point socket for everyday use. Flip socket over and you have a twist socket damaged oil drain plug remover of the same size.

Socket sizes:

- 30114 17 mm socket
- 30114 19 mm, 3/4" socket
- 30114-03 14 mm socket
- 30114-04 15 mm socket
- 30114-05 16 mm, 5/8" socket

Model	Item No.	Drive	Weight
30114	30114	3/8"	3 lbs (1.3 kg)



Six Piece Double-Duty Flip Socket Set

Juego de dados abatibles de doble servicio, seis piezas

Jeu de six douilles inversées double action

One end is a standard 6-point socket for everyday use. Flip socket over and you have a 6-fluted twist socket for removing damaged or rounded wheel lugs.

Socket sizes:

- 30111-01 17 mm socket
- 30111-02 19 mm, 3/4" socket
- 30111-03 21 mm socket
- 30111-04 13/16" socket
- 30111-05 7/8" socket
- 30110-06 3" extension

Model	Item No.	Drive	Weight
30111	30111	1/2"	2.8 lbs (1.2 kg)



Three Piece Lug & Lock Flip Socket Set

Juego de dados abatibles para trabas/ruedas, tres piezas

Jeu de trois douilles de torsion inversées d'arrêt et de roue

One end is a standard 6-fluted twist socket for removing damaged wheel lugs. Flip socket over and you have a 12-fluted twist socket for removing wheel locks.

Socket sizes:

- 30115-02 19 mm, 3/4" socket
- 30115-05 7/8" socket
- 30110-06 3" extension

Model	Item No.	Drive	Weight
30115	30115	1/2"	1.6 lbs (.7 kg)



Impact Extensions

Extensiones de impacto

Rallonges à choc



30110-06



30245

1" sq. dr. male x 1" sq. dr. female 13" impact extension. Provides access to hard-to-reach areas with 1" impact socket applications.



30246

3/4" sq. dr. male x 1" sq. dr. male 13" extension. Provides access to deep budd wheels.

Model	Item No.	Description	Drive	Weight
30110-06	30110-06	3" Impact Extension	1/2"	.4 lbs (.18 kg)
30245	30245	1" Drive x 13" Impact Extension	1/2"	.4 lbs (.18 kg)
30246	30246	3/4" Sq. Dr. Male x 1" Sq. Dr. Male 13" Impact Ext	1/2"	.4 lbs (.18 kg)



SOCKETS AND SOCKET SETS HAVE A


LIMITED LIFETIME WARRANTY

*Thinwall sockets have a two-year warranty with proof of purchase

Deep, Thin Wall Flip Socket

Llave de tubo movable, de paredes finas y profundidad

Douille double tête profonde à paroi étroite



30156

1/2" square drive, black impact socket is deep and thin walled to reach areas conventional sockets won't. Flip socket provides two socket sizes which cover virtually all SAE automotive wheel lug sizes. **Imported.**

Model	Item No.	Socket Sizes	Drive	Weight
30156	30156	3/4", 13/16"	1/2"	.4 lbs (.18 kg)
30158	30158	19 mm, 21 mm	1/2"	.4 lbs (.18 kg)

Universal Emergency Wheel-Lock Remover

Desmontador universal para anillos de seguridad de ruedas de emergencia

Dégageur de bloqueur de roue universel de secours



Removes wheel locks when the key is lost or misplaced. Tapered socket fits over most car wheel locks. Use soft-faced hammer to drive onto wheel lock. Limited use.

Model	Item No.	Drive	Weight
30161	30161	1/2"	1 lb (.5 kg)


Heavy-Duty Impact Sockets

Llaves de tubo de impacto de alta resistencia
Douilles résistantes aux chocs

Special Purpose Impact Sockets Off-Road Budd, Square, SAE, and Metric

Llaves de tubo de impacto especializados para todo terreno tipo Budd, cuadrados, de SAE y métricos

Douilles carrées, SAE, métrique ou pour roues à disques, spécialement conçues pour résister aux chocs



30120

30121

30356

Special 1-1/2" hex deep heavy-duty impact socket designed for outer cap nuts on Budd-style truck wheels. The 1-1/2" hex depth is limited to help prevent socket contact with the wheel. The socket is deep style to eliminate contact with the inner cap nut. **Imported.**

3/4" Drive		1" Drive		Weight
Model	Description	Model	Description	
30120	13/16" square	30149	13/16" square	1.4 lbs (.6 kg)

Combination Budd Wheel - SAE and Metric

Rueda de combinación tipo Budd- SAE y métrica
Deux en un pour roues à disques - SAE et métrique

3/4" Drive		1" Drive		Weight
Model	Description	Model	Description	
30121	1-1/2" x 13/16" square	30150	1-1/2" x 13/16" square	3.1 lbs (1.4 kg)

Deep Length Impact Sockets - SAE and Metric



Llaves de tubo de impacto de longitud profunda- SAE y métrica
Douilles de profonde longueur - SAE et métrique

6 point, 3/4" Drive		6 point, 1" Drive		Weight
Model	Description	Model	Description	
30356	33 mm deep	30366	33 mm deep	1.6 lbs (.7 kg)

Dual Wheel Lug Stud Remover

Desmontador de tuercas para ruedas dobles

Extracteur de goujons de roues de camions à prise double



Special self-tapping splines provide maximum grip to remove stripped lug studs. Use with **TR1, TR98** truck wrenches. Can also be used with an open end wrench. Use with soft faced hammer.(see pg. 39)

Model	Item No.	Description	Weight
30165	30165	Fits 13/16" sq. inner nut	1 lb (.5 kg)

Ken-Tool®
WHEREVER TIRES ARE CHANGED™

Inventors Wanted!

If you have an idea for a new tool please let us know! Your idea could earn you cash or a royalty.

Just visit our website at www.kentool.com/inventors to submit your idea for consideration!

TPMS Sensor Hardware Service Set

Juego de servicio de sensores TPMS

Ensemble d'entretien matériel des capteurs TPMS



Includes Complete Vehicle Application Guide



Includes the TPMS Sentry™ Sensor Service Tool



NO MORE GUESSING!
All of the hardware needed to service most domestic and import TPMS sensors!

Versatile 150-pc assortment (15 unique kits) covers 90-95% of TPMS-fitted vehicles

Each Hardware Kit contains a valve core, valve cap, grommet ferrule nut, gaskets, washers and valve stem (contents specific to each application).

Special Bonus — Ken-Tool's TPMS Sentry™ Sensor Service Tool No. 30209.

Plus 50 extra TPMS approved nickel plated valve cores and 50 extra approved plastic caps.

Replacement Hardware Kits Available From Ken-Tool.

Set No. 30001 Weight: 6 lbs (2.7 kg)

150 Pc. Set with 3" x 9" x 16" Portable Poly Case Includes:



CONTENTS: UNIVERSAL MASTER TPMS SENSOR HARDWARE & SERVICE SET

All replacement kits available separately. Go to www.kentool.com for updated application data.

30001

30010 Infinity, Mitsubishi, Nissan Qty 10	30013 Cadillac, Chevy, Chrysler, Dodge, Infiniti, Isuzu, Jeep, Mitsubishi, Nissan, Subaru Qty 10	30016 Buick, Cadillac, Chevy, GM, GMC, Isuzu, Pontiac, Saab Qty 10	30018 Buick, Cadillac, Chevy, Chrysler, Dodge, GM, GMC, Hyundai, Jaguar, Jeep, Land Rover, Mazda, Mitsubishi, Pontiac, Saturn, Suzuki, Volvo, VW Qty 10
30019 Audi, VW Qty 10	30021 Acura, Honda, Hyundai, Kia Qty 10	30022 Audi, BMW, Land Rover, Mercedes, Mini Cooper, Porsche, VW Qty 10	30023 Acura, Honda, Lexus, Pontiac, Scion, Toyota Qty 10
30024 GMC, Hummer, Lexus, Toyota, VW Qty 10	30026 Buick, Cadillac, Chevy, Chrysler, Dodge, Ford, GM, GMC, Hummer, Jeep, Lincoln, Mazda, Mercury, Pontiac, Saturn, Subaru, Suzuki Qty 10	30027 Ford, Lincoln, Mercedes, Mercury Qty 10	30030 Qty 50
30041 Saab, Saturn, Suzuki, Volvo Qty 10	30042 Chrysler, Dodge, Infiniti, Jeep, Mercedes-Benz, Mitsubishi, Nissan, Smart Car Qty 10	30043 Cadillac, Chevy, GM, GMC Qty 10	30031 Qty 50



© 2012 KEN-TOOL AKRON, OH 44305
 TOLL FREE: 888-536-8656
 SEE OUR VIDEO DEMOS AT WWW.KENTOOL.COM



Also available separately: • También disponible por separado: • Également disponible séparément :




Model	Description	Torque Limit
30060	Valve Core Torque Driver	4 in-lbs
30070	1/4"-drive Variable Ratcheting Torque Wrench	30-150 in-lbs
30080	11mm Deep Socket, 1/4"-drive	
30081	12mm Deep Socket, 1/4"-drive	
30090	Torque Driver & T-10/T-15 TORX® bits	12 in-lbs



WARNING: Always wear safety goggles when using hand tools

Impact Separator Tool

Impacto de la herramienta de separación • Outil impacteur



Heavy-duty impact front end service tool. Hits harder and straighter than a hammer, but no more misses or glancing blows. Two easily interchangeable hardened steel forks. Use the T39B-1 fork to separate shock absorber links and tie rods; Use the T39B-2 fork on spindle support arms to remove ball joints without damaging other suspension parts. Services compact cars and light duty trucks too. Made in USA. Patent Pending. Includes impact separator tool with 2 forks:

35939-01 = T39B-1 Tie Rod Fork, Fork Opening: 5/8" (2 cm)
35939-02 = T39B-2 Ball Joint Fork, Fork Opening: 15/16" (2 cm)

Model	Item No.	Description	Length	Weight
T39B	35939	Impact Separator Tool w/2 forks	36-1/2" (92.71 cm)	9.8 lbs (4.5 kg)

Front End Service Tools

Herramientas para el mantenimiento delantero



Outils de service du train avant

These tools are manufactured from a single piece of alloy steel, forged, and heat-treated for long life. Essential when replacing suspension parts. Striking ends have been enlarged to provide a bigger and safer striking surface. Painted finish for rust resistance. Ken-Tool offers a size and design for all your needs.

Separator Tool • Herramienta separadora • Séparateur



Use to remove camber adjustment sleeves on Ford 4 x 2 and 4 x 4 pickups. Use as Pitman arm wedge on medium and heavy-duty trucks.

Model	Item No.	Length	Stock	Fork Opening	Weight
B36	32036	11" (28 cm)	7/8" (2 cm)	1-7/16" (4 cm)	1.9 lbs (.8 kg)

Pitman Arm Wedge

Cuña para la biela de mando de la dirección
Coin pour bielle pendante



Removes Pitman arms on cars and light trucks.

Model	Item No.	Length	Stock	Fork Opening	Weight
B37	32037	11" (28 cm)	7/8" (2 cm)	1- 1/8" (3 cm)	1.8 lbs (.8 kg)

Shock Link and Tie Rod Separator

Separador de la barra de acoplamiento y la unión del amortiguador
Fourche à barre d'accouplement et articulation d'amortisseur



Use to separate shock absorber links and tie rods.

Model	Item No.	Length	Stock	Fork Opening	Weight
B39	32039	16" (41 cm)	7/8" (2 cm)	5/8" (2 cm)	2.1 lbs (.9 kg)

Ball Joint Separator

Separador de juntas de rótulas • Séparateur de joint à rotule



Use on spindle support arms to remove ball joints without damaging other suspension parts. Services compact cars and light duty trucks.

Model	Item No.	Length	Stock	Fork Opening	Weight
B40	32040	16" (41 cm)	7/8" (2 cm)	15/16" (2 cm)	2.8 lbs (1.2 kg)

MacPherson Strut Coil Spring Compressor Set

Equipo compresor de resorte espiral de montante MacPherson



Groupe compresseur de ressort hélicoïdal à jambe de suspension



Compressor works on most MacPherson Strut assemblies and is for use with replacements. Use the compressor when replacing bent strut or strut tube and damaged spindles. Use it on or off the car. Acme threaded screw for durability. Do not use on General Motors "A", "C", "J", or "X" body cars.

Model	Item No.	Weight
39730	39730	7 lbs (3.1 kg)

Ken-Tool[®]
WHEREVER TIRES ARE CHANGED™

Cross-Pein / Blacksmith Hammer

Martillo de mano/de peña

Marteau à panne de travers/de forgeron

High carbon steel with machine polished face. **Imported.**

Top Grade U.S. Hickory Handle

Mango U.S. Hickory de primera calidad

Manche de qualité supérieure U.S. Hickory

Model	Item No.	Length	Face	Eye Size	Head Weight
85H-3	37103	15" (38 cm)	1-5/8"	1 x 1-3/4"	3 lbs (1.4 kg)

85H-3H 37023 15" (38 cm) Replacement Handle

New England Pattern Hand-Drilling Hammers

Martillos perforadores de mano con patrones de Nueva Inglaterra

Perforateur manuel modèle 'New England'

'New England'

Top grade U.S. hickory handle. **Imported.**

80H-4

Model	Item No.	Length	Face	Eye Size	Head Weight
80H-3	37003	10" (25 cm)	1-1/2"	1 x 3/4"	3 lbs (1.4 kg)
80H-4	37004	10" (25 cm)	1-5/8"	1 x 3/4"	4 lbs (1.8 kg)

85H-3H 37012 10" (25 cm) Replacement Handle for 80H-3, 80H-4

Tire Knockers

Golpeadores de llantas

Bâtons de vérification de pression des pneus

Model	Item No.	Length	Weight
35110	35110	18" (46 cm)	.7 lbs (.3 kg)

Double-Face Sledge Hammers

Mazas dobles

Masses à double-face

High carbon steel, heat treated. Machined, polished face. **Imported.**

Top Grade U.S. Hickory Handle

Mango U.S. Hickory de primera calidad

Manche de qualité supérieure U.S. Hickory

Model	Item No.	Length	Face	Eye Size	Head Weight
84H-2	37302	15" (38 cm)	1-1/2"	3/4" x 1"	2.5 lbs (1.1 kg)
84H-4	37304	15" (38 cm)	1-3/4"	3/4" x 1"	4 lbs (1.8 kg)
84H-8	37308	36" (91 cm)	2"	1" x 1-3/8"	8 lbs (3.6 kg)
84H-10	37310	36" (91 cm)	2-1/8"	1" x 1-3/8"	10 lbs (4.5 kg)
84H-12	37312	36" (91 cm)	2-1/8"	1" x 1-3/8"	12 lbs (5.4 kg)
84H-16	37316	36" (91 cm)	2-3/8"	1" x 1-3/8"	16 lbs (7.2 kg)
84H-20	37320	36" (91 cm)	3"	2" x 1.5"	20 lbs (9 kg)

85H-3H 37023 15" (38 cm) Replacement Handle for 85H-3, 84H-2, 84H-4

84H-8H 37025 36" (91 cm) Replacement Handle for 84H-8, 84H-10, 84H-12, 84H-16

84H-20H 37089 36" (91 cm) Replacement Handle for 84H-20

2 lb. Rubber Mallet

Mazo de goma de 2 libras

Maillet en caoutchouc de 2 lb

Rubber head minimizes marring surfaces.

Model	Item No.	Handle Length	Head Weight
T32	35310	17" (43 cm)	2 lbs (.9 kg)

WARNING: Always wear safety goggles when using striking or struck tools. Never use one hammer to strike another hammer. Never use a tool with a loose or damaged handle. Discard any striking or struck tool if tool shows dents, cracks, chips, or mushrooming.

Aligning & Pry Bars

Alineación y palancas

Leviers & barras d'alignement

Aligning Bars

Barras de alineación • Barres d'alignement

A forged, alloy steel, heat-treated bar that can be used for prying, aligning and positioning many heavier jobs in the shop. The finish is black oxide.

Model	Stock	Length	Weight
7025	5/8" (16 mm)	18" (45.7 cm)	1.4 lbs (.6 kg)
7026	3/4" (19 mm)	20" (50.8 cm)	2.3 lbs (1 kg)
7027	3/4" (19 mm)	24" (61 cm)	2.8 lbs (1.3 kg)
7028	7/8" (22 mm)	30" (76.2 cm)	5 lbs (2.3 kg)

Close Quarters Bars

Barras de cuartos cerrados • Barres à distance rapprochée

These bars are made of forged, alloy steel, and heat-treated. Designed for use in tight spots, their balanced construction provides very powerful leverage. The finish is black oxide.

Model	Stock	Length	Weight
7030	3/8" (10 mm)	9" (22.9 cm)	.31 lbs (.14 kg)
7031	1/2" (13 mm)	16" (40.6 cm)	.89 lbs (.4 kg)
7032	5/8" (16 mm)	18" (45.7 cm)	1.5 lbs (.7 kg)

Die Setter Bars

Barras troqueladoras • Barres de monteur de matrices

A practical and useful shop tool for the quick separation of punch and die holder. The bars are made of forged, alloy steel and heat-treated for strength. The finish is black oxide.

Model	Stock	Length	Weight
7035	5/8" (16 mm)	18" (45.7 cm)	1.7 lbs (.8 kg)
7037	3/4" (19 mm)	30" (76.2 cm)	4.2 lbs (1.9 kg)

Dead Blow Hammers

Martillos de golpe seco • Masse sans rebond

Head is shot filled for maximum force with no bounce effect. Safest non-marring, non-sparking hammers available. Great for tire changing and general shop use. High quality materials to withstand years of hard use.

Economy Strike Pro®

Económico • Économique

Dead blow action in high visibility colors.

Model	Item No.	Color	Length	Nominal Weight
T335	35335	Safety Yellow	12" (31 cm)	1 lb (.5 kg)
T336	35336	Safety Orange	12" (31 cm)	1.5 lbs (.7 kg)

Professional Dead Blow

Martillo de golpe seco profesional

Masse professionnelle sans rebond

Power-drive fiberglass handle gives 20% more driving power, yet reduces user fatigue. One-pound dead blow hammer is especially useful for truck wheel weights.

Model	Item No.	Description	Length	Nominal Weight
TG331	35331	1 lb Head (.5 kg)	12-1/4" (31 cm)	1.8 lbs (.8 kg)
TG332	35332	2 lb Head (.9 kg)	13-1/2" (34 cm)	1.9 lbs (.9 kg)
TG333	35333	3 lb Head (1.4 kg)	14-1/2" (37 cm)	2.7 lbs (1.2 kg)
TG334	35334	4 lb Head (1.8 kg)	15-1/2" (40 cm)	3.4 lbs (1.5 kg)
TG337	35337	Steel Face / Soft Face	13-1/2" (34 cm)	2.2 lbs (1 kg)

Bendix® ADB22X™ Air Disc Brake Tool Kits

These kits provide specialized tools for the replacement of Bendix® air disc brake tappet and boot assemblies, tappet inner seals, and guide pins and boots.

No. 80000 ADB22X Complete Kit (Bendix #K029164)

Juego completo No. 80000 ADB22X (Bendix No. K029164)

Kit complet ADB22X No. 80000 (Bendix #K029164)

Kit No. 80000 Weight: 22 Lbs (10 kg).

Includes Kit No. 80001 and Kit No. 80002 listed below:

Tappet & Boot Replacement Tool Kit (Bendix #K028829)

Juego de herramientas de reemplazo de balancines y capuchones (Bendix No. K028829)

Kit d'outillage de remplacement de poussoir et de démarrage (Bendix #K028829)

Kit No. 80001 Weight: 7 Lbs (3.2 kg).

7 Pc. Set Includes:

Bendix No.	Ken-Tool No.	Description
T1	80101	KT01 Cup
T2	80102	KT02 Handle for KT01 Cup
T3	80103	KT03 Swivel assy. made up of KT03-1 Short Body, KT03-2 Brass Disc, and KT03-3 Retaining Spring
T4	80104	KT04 Long Strut
T9	80109	KT09 Flange
T15	80115	KT15 Fork
T24	80124	KT24 Black Nylon Disc



No. 80001

See page 25 of Bendix Service Manual listed below*

Guide Pin / Pin Boot Service Tool Kit (Bendix #K029107)

Juego de herramientas para servicio del pasador guía/capuchón del pasador (Bendix No. K029107)

Kit d'outillage d'entretien de broche de démarrage / broche de guidage (Bendix #K029107)

Kit No. 80002 Weight: 15 Lbs (6.8 kg).

13 Pc. Set Includes:

Bendix No.	Ken-Tool No.	Description
T05	80105	KT05 1-3/8" Black Disc
T06	80106	KT06 1-1/2" Black Disc
T07	80107	KT07 2" Dia. Sleeve
T08	80108	KT08 2-1/8" Dia. Disc
T10	80110	KT10 8" Bolt
T12	80112	KT12 3-7/8" Long Sleeve
T13	80113	KT13 10" Bolt
T14	80114	KT14 Brass Nut
T16	80116	KT16 Dimpling Tool made up of KT16-1 Main Body, KT16-2 Crimper Screw, KT16-3 Expansion Ring, KT16-4 Plunger, KT16-5 Dimpling Pins, and KT16-6 Set Screw
T20	80120	KT20 8" Bolt
T21	80121	KT21 Half Sleeve
T26	80126	KT26 Cap Tool made up of KT26-1 Retaining Ring, KT26-2 Mandrel and KT26-3 Sleeve
T27	80127	KT27 Cap Tool made up of KT26-1 Retaining Ring, KT26-2 Mandrel and KT27-3 Sleeve



No. 80002

See page 30 of Bendix Service Manual listed below*

*For detailed instructions see the Bendix ADB22X service manual SD-23-7541 on the "Manuals and Parts Lists" link at www.kentool.com

CROSS-REFERENCE BY PART NUMBER

ITEM NO.	MODEL NO.	PAGE NO.	ITEM NO.	MODEL NO.	PAGE NO.	ITEM NO.	MODEL NO.	PAGE NO.	ITEM NO.	MODEL NO.	PAGE NO.	ITEM NO.	MODEL NO.	PAGE NO.	ITEM NO.	MODEL NO.	PAGE NO.
7025		43	30206		36	31439		24	32445	T2122Y24	15	34746	T46	12	35659	T59	26
7026		43	30207		36	31440		22	32450	T1920F24	15	34747	T46A	12	35661	T61	26
7027		43	30208		36	31444		5	32451	T1922F24	15	34748	T46B	12	35662	T62	26
7028		43	30209		16	31446		24	32452	T2022F24	15	34749	T46C	12	35663	T63	26
7030		43	30211		36	31551	T51	24	32453	T1921F24	15	34846	T47	12	35690	T90	26
7031		43	30212		36	31554	T54	24	32454	T2021F24	15	34847	T47A	12	35695	T95	26
7032		43	30213		36	31564		24	32455	T2122F24	15	34848	T47B	12	35696	T96	26
7035		43	30214		36	31565	T65	25	32501	TR1	28	34849	T47C	12	35697	T95A	26
7037		43	30215	T16P	24	31566	T66	25	32502	TR2	28	34950	T950	18	35795	TM95	26
7326		33	30216		36	31567	T67	25	32503	TR3	28	35104	T11RH	39	35805	D105A	823
7326U		33	30217		36	31568	T68	25	32505	TR3A	28	35105	T34RH	39	35837		23
29980		3	30218		36	31710		4, 11, 13, 14, 18	32506	TR3X	28	35110		43	35839		23
29981		3	30219		36	31713		4, 11, 18	32508	TR98	28	35111	T11BH	21	35840		23
29995		8	30220		36	31714		18	32509	TR9	28	35113	T11HN	21	35847	T147A	23
30000		16	30221		36	31810		4, 11, 13, 14, 18	32512	TR2A	28	35119	T11CH	21	35847S		23
30001		41	30222		36	31820	T22R	10,11	32519	TR99	28	35127	T11DH	21	35848		4, 11, 23
30101		38	30223		36	31830	T1920Z18	15	32551	TRM1	28	35129	T11EH	21			
30102		38	30224		36	31831	T1922Z18	15	32552	TRM2	28	35131	T11EHS	21	35924	T24B	19
30103		38	30225		36	31832	T2022Z18	15	32553	TRM3	28	35201	T12B	21	35926	T26B	19
30106		38	30226		36	31833	T1921Z18	15	32556	TRM6	28	35202	T12D	21	35934	T34B	20
30107		38	30227		36	31834	T2021Z18	15	32557	TRM7	28	35206	TG31H	21	35935		20
30108		37	30228		36	31835	T2122Z18	15	32559	TRM6A	28	35211	TG11BH	21	35936	T36B	20
30109		37	30229		36	31840	T1920Y18	15	32610		28	35219	TG11CH	21	35939	T39B	42
30110		39	30230		36	31841	T1922Y18	15	33020	T21A	10,11	35227	TG11DH	21	35998	T98	19
30111		39	30231		36	31842	T2022Y18	15	33021	T22A	10,11	35229	TG11EH	21	36001	T101	31
30112		39	30232		36	31843	T1921Y18	15	33022	T19M	16	35230	T11KH	21	36002	T102	31
30113		39	30233		36	31844	T2021Y18	15	33023	T20M	16	35310	T32	43	36003	T103	31
30114		39	30234		35	31845	T2122Y18	15	33024	T21M	10,11	35311	T11B	21	36004	T104	31
30115		39	30235		36	31850	T1920X18	15	33025	T22M	10,11	35317	T33R	21	36005	T105	31
30116		37	30236		36	31851	T1922X18	15	33026	T22HD	10,11	35321	T34	21	36006	T106	31
30117		37	30237		36	31852	T2022X18	15	33050	T1920A30	15	35323	T35	21	36007	T101A	31
30118		37	30238		36	31853	T1921X18	15	33051	T1922A30	15	35325	T36	21	36011	T111	6
30119		39	30239		36	31854	T2021X18	15	33052	T2022A30	15	35327	T11D	20	36014	T114	32
30120		40	30240		36	31855	T2122X18	15	33053	T1921A30	15	35329	T11E	20	36015	T115	32
30121		40	30241		36	32036	B36	42	33054	T2021A30	15	35330	T11EHS	20	36016		32
30149		41	30242		36	32037	B37	42	33055	T2122A30	15	35331	TG331	43	36017		32
30150		41	30243		36	32039	B39	42	33060	T1920M30	15	35332	TG332	43	36045		30
30151		38	30244		36	32040	B40	42	33061	T1922M30	15	35333	TG333	43	36046		30
30152		38	30245		39	32101	T1X	16	33062	T2022M30	15	35334	TG334	43	36047		29
30153		38	30246		39	32102	T2X	16	33063	T1921M30	15	35335	T335	43	37003	80H-3	43
30154		38	30247		36	32106	T6A	16	33064	T2021M30	15	35336	T336	43	37004	80H-4	43
30156		40	30248		36	32109	T9A	16	33065	T2122M30	15	35337	TG337	43	37012	80H-3H	21, 43
30158		41	30249		36	32110	T9C	16	33195		11	35354	B230	24	37023	85H-3H	21, 43
30161		40	30250		36	32114		16	33196		11, 18	35355	B232	24	37025	84H-8H	21, 43
30165		40	30251		36	32115	T5	16	33199		4, 11, 18	35364		29	37089	84H-20H	21, 43
30170		37	30255		36	32116	T16A	16	33219	T19A	16	35411	TG11B	21	37103	85H-3	43
30171		37	30256		36	32117	T16C	16	33220	T20A	16	35417	TG33R	21	37302	84H-2	43
30174		35	30257		36	32118	T8	16	33223	T23A	17	35421	TG34	21	37304	84H-4	43
30175		35	30258		36	32119	T19	16	33224	T23B	17	35423	TG35	21	37308	84H-8	43
30176		35	30259		10	32120	T20	16	33238	T38	16	35425	TG36	21	37310	84H-10	43
30179		35	30270		38	32121	T21R	16	33239	T39	16	35427	TG11D	20	37312	84H-12	43
30180		35	30271		38	32123	T23	17	33341	T41	19	35429	TG11E	20	37316	84H-16	43
30181		36	30299		36	32125	T25	17	33342	T42	19	35440		4, 11	37320	84H-20	43
30182		36	30356		41	32126	T26A	19	34121	T21F	16	35442		11	38600	T600	42
30183		36	30366		41	32127	T27	17	34122	T21HD	16	35446		14	38601	T601	42
30184		36	30512		4, 11, 23	32128	T27A	17	34401	TR10	28	35447	T2005	14	38620		22
30185		36	30511	B111	23	32129		17	34402	TR11	28	35448	T2006	14	39604	KT-4	34
30186		36	30515	T15	24	32130		17	34420		28	35449	T2001	13	39606	KT-6	34
30187		36	30605		28	32131		17	34543	TR43	27	35450	T2002	13	39608	KT-8	34
30188		36	30606		25	32318	TR5	28	34545	TR44X	27	35453		13	39730		42
30189		36	30609	TX9	25	32319	TR5A	28	34547	TR44SW	27	35460	T11K	20	39760		9
30190		35	30610	TX10	25	32420	T22F	10,11	34549		7	35529	T11AH	21	39805	T43A	16
30195		36	30612	TX12	25	32430	T1920Z24	15	34644	T45A-2000K	12	35595	TC95	26	39806	T43C	16
30196		36	30618	TX200	25	32431	T1922Z24	15	34645	T45A	12	35620	T9520	26	39808	T44	16
30197		36	30619	TX241	25	32432	T2022Z24	15	34645C	T45AC	4, 11, 12	35630		27	39810	T43D	16
30198		36	30620	TX50	25	32433	T1921Z24	15	34647	T45HD	36	35633		27	39998		23
30199		36	30649		10	32434	T2021Z24	15	34648	T48A	17	35634		27	64055	K55	34
30200		36	31361	X161	24	32435	T2122Z24	15	34649	T45ASD	12	35635		27	64065	K65	34
30201		36	31431	T131	24	32440	T1920Y24	15	34652	T52	19	35637		27	64650	KT4650	34
30202		36	31432	T132	24	32441	T1922Y24	15	34670	T100	19	35638		27	64800	KT4800	34
30203		36	31433	T133	24	32442	T2022Y24	15	34672	TS72	22	35648		30	80000		44
30204		36	31437		24	32443	T1921Y24	15	34674	TS74	22	35656	T56	26	80001		44
30205		36	31438		24	32444	T2021Y24	15	34678	TS42	40	35657	T57	26	8002		44

CROSS-REFERENCE BY MODEL NUMBER

ITEM NO.	MODEL NO.	PAGE NO.	ITEM NO.	MODEL NO.	PAGE NO.	ITEM NO.	MODEL NO.	PAGE NO.	ITEM NO.	MODEL NO.	PAGE NO.
37003	80H-3	43	33223	T23A	17	35336	T336	43	35334	TG334	43
37012	80H-3H	21	33224	T23B	17	38600	T600	40	35337	TG337	43
37004	80H-4	43	35924	T24B	19	38601	T601	40	35795	TM95	26
37310	84H-10	43	32125	T25	17	34950	T950	18	32501	TR1	28
37312	84H-12	43	32126	T26A	19	35620	T9520	28	32502	TR2	28
37316	84H-16	43	35926	T26B	19	33050	T1920A30	15	32512	TR2A	28
37302	84H-2	43	32127	T27	17	32450	T1920F24	15	32503	TR3	28
37320	84H-20	43	32128	T27A	34	33060	T1920M30	15	32505	TR3A	28
37304	84H-4	43	35310	T32	43	31850	T1920X18	15	32506	TR3X	28
37308	84H-8	43	35317	T33R	21	31840	T1920Y18	15	32318	TR5	28
37025	84H-8H	21, 43	35321	T34	21	32440	T1920Y24	15	32319	TR5A	28
37089	84H-20H	21, 43	35934	T34B	20	31830	T1920Z18	15	32509	TR9	28
37103	85H-3	38	35105	T34RH	21	32430	T1920Z24	15	34401	TR10	28
37023	85H-3H	21, 43	35323	T35	21	33053	T1921A30	15	34402	TR11	28
30511	B111	23	35325	T36	21	32453	T1921F24	15	34543	TR43	27
35354	B230	24	35936	T36B	20	33063	T1921M30	15	34547	TR44SW	27
35355	B232	24	33238	T38	16	31853	T1921X18	15	34545	TR44X	27
32036	B36	42	33239	T39	16	31843	T1921Y18	15	32508	TR98	28
32037	B37	42	35939	T39B	42	32443	T1921Y24	15	32519	TR99	28
32039	B39	42	33341	T41	19	31833	T1921Z18	15	32551	TRM1	28
32040	B40	42	33342	T42	19	32433	T1921Z24	15	32552	TRM2	28
35805	D105A	8	39805	T43A	16	33051	T1922A30	15	32553	TRM3	28
64055	K55	34	39806	T43C	16	32451	T1922F24	15	32556	TRM6	29
64065	K65	34	39810	T43D	16	33061	T1922M30	15	32559	TRM6A	28
39604	KT-4	34	39808	T44	16	31851	T1922X18	15	32557	TRM7	28
39606	KT-6	34	34645	T45A	12	31841	T1922Y18	15	34678	TS42	22
39608	KT-8	34	34644	T45A-2000K	12	32441	T1922Y24	15	34672	TS72	22
64650	KT4650	34	34645C	T45AC	4, 11, 12	31831	T1922Z18	15	34674	TS74	22
64800	KT4800	34	34649	T45ASD	12	32431	T1922Z24	15	30609	TX9	25
32101	T1X	16	34647	T45HD	12	35449	T2001	13	30610	TX10	25
32102	T2X	16	34746	T46	12	35450	T2002	13	30612	TX12	25
32115	T5	16	34747	T46A	16	35447	T2005	14	30620	TX50	25
32106	T6A	16	34748	T46B	12	35448	T2006	14	30618	TX200	25
32118	T8	16	34749	T46C	12	33054	T2021A30	15	30619	TX241	25
32109	T9A	16	34846	T47	12	32454	T2021F24	15	31361	X161	24
32110	T9C	16	34847	T47A	12	33064	T2021M30	15			
35529	T11AH	21	34848	T47B	12	31854	T2021X18	15			
35311	T11B	21	34849	T47C	12	31844	T2021Y18	15			
35111	T11BH	21	34648	T48A	34	32444	T2021Y24	15			
35119	T11CH	21	31551	T51	24	31834	T2021Z18	15			
35327	T11D	20	34652	T52	19	32434	T2021Z24	15			
35127	T11DH	21	31554	T54	24	33052	T2022A30	15			
35329	T11E	20	35656	T56	26	32452	T2022F24	15			
35129	T11EH	21	35657	T57	26	33062	T2022M30	15			
35131	T11EHS	21	35659	T59	26	31852	T2022X18	15			
35330	T11ES	20	35661	T61	26	31842	T2022Y18	15			
35113	T11HN	21	35662	T62	26	32442	T2022Y24	15			
35460	T11K	20	35663	T63	26	31832	T2022Z18	15			
35230	T11KH	21	31565	T65	25	32432	T2022Z24	15			
35104	T11RH	21	31566	T66	25	33055	T2122A30	15			
35201	T12B	21	31567	T67	25	32455	T2122F24	15			
35202	T12D	21	31568	T68	25	33065	T2122M30	15			
30515	T15	24	35690	T90	26	31855	T2122X18	15			
32116	T16A	16	35695	T95	26	31845	T2122Y18	15			
32117	T16C	16	35697	T95A	26	32445	T2122Y24	15			
30215	T16P	24	35696	T96	26	31835	T2122Z18	15			
32119	T19	16	35998	T98	19	32435	T2122Z24	15			
33219	T19A	16	34670	T100	19	35595	TC95	26			
33022	T19M	16	36001	T101	31	35411	TG11B	21			
32120	T20	16	36007	T101A	31	35211	TG11BH	21			
33220	T20A	16	36002	T102	31	35219	TG11CH	21			
33023	T20M	16	36003	T103	31	35427	TG11D	20			
33020	T21A	10,11	36004	T104	31	35227	TG11DH	21			
34121	T21F	16	36005	T105	31	35429	TG11E	20			
34122	T21HD	16	36006	T106	31	35229	TG11EH	21			
33024	T21M	10,11	36011	T111	6	35206	TG31H	21			
32121	T21R	16	36014	T114	32	35417	TG33R	21			
33021	T22A	10,11	36015	T115	32	35421	TG34	21			
32420	T22F	10,11	31431	T131	24	35423	TG35	21			
33026	T22HD	10,11	31432	T132	24	35425	TG36	21			
33025	T22M	10,11	31433	T133	24	35331	TG331	43			
31820	T22R	10,11	35847	T147A	8	35332	TG332	43			
32123	T23	17	35335	T335	43	35333	TG333	43			



Throughout this catalog watch for YouTube symbols that indicate one or more videos are available for the product you are reviewing. Then go to www.youtube.com/kentoolvideomedia to find a selection of videos for our products. You can also scan the barcode with your Smartphone to get a link to our YouTube videos or details on how to Contact Us at Ken-Tool.

We believe all Ken-Tool customers should be satisfied with the performance, quality and workmanship of whatever product they buy. All Ken-Tool products are warranted against defects in materials and workmanship for one year from the date of purchase. Any Ken-Tool branded product that fails to perform its intended function, due to a defect in workmanship or materials will, at our option, be replaced or repaired free of charge. Warranty claims for items that have broken or are no longer useful due to normal wear, misuse, abuse, alteration, grinding, or heating, will not be honored. Proof of purchase including the purchase date is required for warranty consideration. Please contact Ken-Tool by phone or email if you have a warranty claim.

Distributed By:



768 E. North Street, P.O. Box 9320
Akron, Ohio 44305

Phone: 330-535-7177 • Fax: 330-535-1345

E-mail: sales@kentool.com

www.kentool.com