



PROFESSIONAL LIFTING EQUIPMENT

# WHEN SAFETY DEPENDS ON PERFORMANCE!

## 72080A

**20 Ton Capacity  
Standard Height  
Air Operated  
Hydraulic Jack**

## 72090A

**20 Ton Capacity  
Low Height  
Air Operated  
Hydraulic Jack**

### INTENDED USE

*Heavy duty truck, agricultural and heavy construction equipment. Ideal for loaded truck and trailer roadside service calls.*



**The NORCO Difference:**  
Its light weight makes it perfect for mobile repair service.

### FEATURES

- Its light weight makes it perfect for mobile repair service.
- Long handle with 36-1/2" reach helps in positioning jack under vehicles with low overhang.
- May be stored in a vertical position.
- Compact design fits easily between tandem wheels.
- Parkerized coating on pump piston, extension screw and extension adapters and chrome coated ram offer protection against rust.
- Removable extension screw is used with the two 4" extension adapters (included) for added height when necessary.
- Self-retracting ram eliminates manual lowering of the jack.
- 5 1/4" diameter high impact composite wheels make maneuverability easy.
- Fast efficient air pump reduces lifting time and has a built-in relief mechanism which prevents the jack from being used beyond its maximum allowable capacity.
- Convenient push button air valve connected to an in-line filter prohibits contaminants from entering the air/hydraulic system.

MODEL NUMBER	CAPACITY	LIFT HEIGHT		STROKE	SCREW EXTENSION	BASE SIZE	P.S.I. RANGE	SHIPPING WEIGHT
		Low	High					
<b>72080A</b>	<b>20 Ton</b>	11.125"	28.625"	6.75"	2.75"	9.25" x 17.25"	100-130	70 lbs.
<b>72090A</b>	<b>20 Ton</b>	8.625"	22.75"	4.125"	2"	9.25" x 17.25"	100-130	63 lbs.