



PROFESSIONAL LIFTING EQUIPMENT

# WHEN SAFETY DEPENDS ON PERFORMANCE!

**925009A**

## 2,850 P.S.I. Single-Speed Steel Hand Pump

### INTENDED USE

For many applications including shop, agricultural, automotive/truck service needs and construction maintenance applications where high pressure pumps are required to activate cylinders rated as high as 55 ton capacity.



### FEATURES

- 3/8 NPT hose connection on all pumps.
- Internal pressure relief valves for overload protection.
- External load release valve for single-acting cylinder operation.

PUMP TYPE				MODEL NUMBER	PRESSURE RATING (P.S.I.)		USABLE OIL CAP. (Cu. In.)	OIL DISPLACEMENT PER STROKE (Cu. In.)		MAXIMUM HANDLE EFFORT (Lbs.)	PISTON STROKE (in.)	DIMENSIONS (Inches)			PUMP HANDLE ARC	WEIGHT (Lbs.)
Single Speed	Two Speed	Steel	Light Weight		1st. Stage	2nd. Stage		1st. Stage	2nd. Stage			Length	Width	Height		
●		●		<b>925009A</b>	2,850	—	18	.16	—	57	.81	13.38	5.25	5.25	40°	11
●		●		<b>925010A</b>	10,000	—	40	.16	—	111	.81	23	5.25	5.25	40°	13
	●		●	<b>925011</b>	200	10,000	55	.687	.151	93	1.00	21.63	4.75	7	50°	9
●			●	<b>925012A</b>	10,000	—	55	.151	—	85	1.00	21.63	4.75	7	50°	9
	●	●		<b>925013B</b>	350	10,000	134	.99	.15	104	1.00	22.5	5.75	7	50°	24
	●		●	<b>925014</b>	400	10,000	155	2.40	.151	95	1.00	21.75	4.75	9	50°	22