# 31 Incorporated P.O. Box 278 Newcomerstown, OH 43832 USA (740) 498-8324

## **MATERIAL SAFETY DATA SHEET**

24 Hour Emergency Service: CHEM•TEL INC. (800) 255-3924

#### I. IDENTIFICATION

PRODUCT NAME: Solvent Cement #14-108 & #14-132

CHEMICAL FAMILY: Rubber Compound CHEMICAL NAME: Heptane Natural Rubber

N/A MOLECULAR WEIGHT: N/A FORMULA:

EDP #0108 SYNONYMS:

**DEPARTMENT OF:** HAZARD CLASSIFICATION NOS. CFR 49 TRANSPORTATION: **CFR 49** SHIPPING NAME: Rubber Compound

N/A CAS NAME: N/A CAS#:

#### **II. PHYSICAL DATA**

**BOILING POINT:** 200° - 209° F FREEZING POINT: N/A SPECIFIC GRAVITY: N/A VAPOR PRESSURE AT 20° C.: N/A

VAPOR DENSITY: N/A **EVAPORATION RATE:** 4.50

PERCENT VOLATILES BY VOLUME: 75 - 85 SOLUBILITY IN WATER (% BY WEIGHT): N/A

APPEARANCE AND ODOR: Cloudy liquid with solvent odor

## **III. INGREDIENTS**

MATERIAL	%	TLV UNITS	HAZARD	CAS#
Heptane	90 – 92	400 PPM	Not Hazardous	142-82-5
Methylcyelohexane	0.5	400 PPM		108-87-2
Uncured Natural Rubber	8 – 10			N/A

### IV. FIRE AND EXPOSURE HAZARD DATA

FLASH POINT (TEST METHODS): 14F (TCC)

FLAMMABLE LIMITS IN AIR (% BY VOLUME): LOWER: 1.0 ; UPPER: 7.0

**EXTINGUISHING MEDIA:** Foam, CO2, Dry Chemical, Fire Fighting Apparatus

SPECIAL FIRE FIGHTING PROCEDURES: Use of self contained breathing apparatus is recommended

for fire fighters

UNUSUAL FIRE & HAZARD EXPLOSION HAZARDS: Extremely flammable and may be ignited by heat,

sparks, flame or other source of ignition.

# 31 Incorporated P.O. Box 278 Newcomerstown, OH 43832 (740) 498-8324

Solvent Cement #14-108 & #14-132

Page 2

#### V. HEALTH HAZARD DATA

EXPOSURE LIMITS TLV, PEL, AND SOURCE: See Section III

**ACUTE EFFECTS OF OVEREXPOSURE:** 

SWALLOWING: May cause irritation of gastrointestinal tract, seek medical attention immediately.

DO NOT give anything by mouth or induce vomiting.

SKIN ABSORPTION: May cause irritation

INHALATION: May cause dizziness, move victim to fresh air, seek medical attention immediately

SKIN CONTACT: May cause irritation upon prolonged or repeated contact EYE CONTACT: May cause eye irritation, flush eyes with clean water

CHRONIC EFFECTS OF OVEREXPOSURE: N/A OTHER HEALTH HAZARDS: N/A

#### **EMERGENCY & FIRST AID PROCEDURES**

SWALLOWING:DO NOT induce vomiting. Seek immediate medical advice and / or medical attention

SKIN: Wash with soap & large quantities of water. Seek medical attention if irritation persists

INHALATION: Give Oxygen

EYES: Flush with large quantities of water for at least 15 minutes. Seek medical attention

PRIMARY ROUTE OF ENTRY: Contact - Inhalation

NOTE TO PHYSICIAN: Inhalation- If breathing is difficult, dizziness or lightheadedness occur when working

in areas with high vapor concentrations, victim should seek air free of vapors. If continued breathing difficulties occur, administer oxygen until

medical assistance can be rendered.

#### **VI. REACTIVITY DATA**

**STABILITY** 

UNSTABLE: X CONDITIONS TO AVOID: N/A

INCOMPATIBILITY (MATERIALS TO AVOID): Strong acids or bases and selected amines.

HAZARDOUS COMBUSTION OR DECOMPOSITION PRODUCTS: Thermal decomposition in the presence

of air may yield carbon monoxide and / or carbon dioxide.

HAZARDOUS POLYMERIZATION

MAY OCCUR: WILL NOT OCCUR: X CONDITIONS TO AVOID: N/A

### VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Stop flow. Recover what is possible. Small amounts of spilled material may be taken up with inert material.

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations.

## **VIII. SPECIAL PROTECTION INFORMATION**

RESPIRATORY PROTECTION (SPECIFY TYPE): Use NIOSH approved cartridge or gas mask

VENTILATION: Mechanical ventilation to keep product within specified TLV ranges PROTECTIVE GLOVES: Imperable gloves advised. EYE PROTECTION: Safety glasses

OTHER PROTECTIVE EQUIPMENT: Work clothes

# 31 Incorporated P.O. Box 278 Newcomerstown, OH 43832 (740) 498-8324

Solvent Cement #14-108 & #14-132

Page 3

#### IX. SPECIAL PRECAUTIONS

#### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Keep product containers cool. Use and store this product with adequate ventilation.

#### OTHER PRECAUTIONS:

Personnel should avoid inhalation of vapors. Personal contact with the product should be avoided. If contact is made, remove saturated clothing and flush affected areas with water.

### X. CARCINOGEN EVALUATION

None of the raw material components of this product are known or suspected to be carcinogens.

#### XI. MSDS PREPARATION INFORMATION

THIS MSDS WAS PREPARED BY:

Charles Muhs
Technical Advisor
31 Incorporated
100 Enterprise Drive
Newcomerstown, OH 43832

THIS MSDS WAS LAST UPDATED ON: (DATE) Jan. 1, 2010

XII. HMIS RATING

HEALTH: FLAMMABILITY: REACTIVITY: PERSONAL PROTECTIVE EQUIP.:

1 0 A

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. VENDOR ASSUMES NO RESPONSIBILITY FOR INJURY TO VENDEE OR THIRD PERSONS PROXIMATELY CAUSED BY THE MATERIALS IF REASONABLE SAFETY PROCEDURES ARE NOT ADHERED TO AS STIPULATED IN THE DATA SHEET. ADDITIONALLY, VENDOR ASSUMES NO RESPONSIBILITY FOR INJURY TO VENDEE OR THIRD PERSONS PROXIMATELY CAUSED BY ABNORMAL USE OF THE MATERIAL, EVEN IF REASONABLE SAFETY PROCEDURES ARE FOLLOWED. FURTHERMORE, VENDEE ASSUMES THE RISK IN HIS USE OF THE MATERIAL.