

# SLICK



## TECHNICAL DATA SHEET

## SLICK Tire Mounting Lubricant

### SPECIFICATIONS

**Physical Form**

Clear Viscous Liquid

**Color**

Purple

**Scent**

None

**Specific Gravity**

1.00

**Density**

8.34 lbs. per gallon

**Foam Test 1% Solution**

Initial - 90mm

**pH 2%**

8.39

**Active Alkalinity as Na<sub>2</sub>O**

0.834%

**Total Alkalinity as Na<sub>2</sub>O**

0.854%

**Solids**

4.06%



Water-based lubricant for quick mounting and dismounting of tires.

Viscous formula will not just run off without doing the job.

### ADVANTAGES

- Concentrated. Mixes easily and completely with water. Will not separate.
- Contains rust inhibitor to prevent rusting of rims.
- Tire adheres to rim. Will not slip.
- Helps to seal tire bead. Reduces bead damage.
- Will not gum up the bead or rim to hinder its future use.
- Reduces friction. Saves wear and repair on tire changers.
- Contains no soap or petroleum products.

### DIRECTIONS

Use "as is" (concentrated) or will go 3 times further when diluted with 2 parts water.

#### MOUNTING TIRE

Swab on bead area thoroughly. Mount the tire onto the wheel and inflate.

#### DISMOUNTING TIRE

Swab the bead and rim with only enough to assist in easy dismounting of the tire.

**CAUTION:** May cause severe irritation to eyes & skin. Harmful if swallowed. Keep out of reach of children.

#### SHIPPING WEIGHT IN POUNDS:

Case 4 Plastic Gallons	35.5 pounds
5 Gallon Plastic Pail	44.2 pounds

